

# DS-265



## Closed cell backer rod for joint sealant support



### ■ PROPERTIES

Round backer rod made of foam that is highly flexible and compressible with non-stick properties. It ensures the mobility of every type of sealant with a simple and easy installation method.

### ■ APPLICATIONS

The backerrod DS-265 of DUROSTICK adjusts the depth of the joint, based on the specs of the project..

### ■ USE

Using a vacuum or a brush, thoroughly clean the joint from dust and debris. Calculate so that the diameter of the backer rod is 25% larger than the width of the joint.

Insert the backer rod to the joint carefully to avoid damaging it. Do not use sharp tools. Excessive elongation of the backer rod is also not recommended. Continue by applying the suitable sealant for the project.

### ■ STORAGE

Store in dry places, protected from the sun, indefinitely.

### ■ PACKAGING

600 meter roll with a diameter of 10mm  
150 meter roll with a diameter of 20mm

### TECHNICAL SPECIFICATIONS

■ Form - Color	Closed cell foam rod - Gray
■ Chemical base	Extruded closed cell polyethylene
■ Water absorption	≤ 0.1
■ Density	20kg/m3±5%

### DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,  
PAINTS & MORTARS

**ATHENS:** ASPROPYRGOS, ATTICA, GR: 193 00,  
Tel: +30 211 60 03 500-599, +30 210 55 16 500,  
+30 210 55 98 350, Fax: +30 210 55 99 612

**THESSALONIKI:** INDUSTRIAL PARK-SINDOS, S.B. 44,  
STREET, DA 10, GR: 570 22,  
Tel: +30 2310 795 797, +30 2310 797 365,  
Fax: +30 2310 797 367

Email: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.