DUROSEAL 600



Professional cartridge and 'sausage' barrel gun



■ PROPERTIES

Professional gun from heavy duty aluminum, for easy sealant applications. It features a heavy-duty spring-loaded trigger and mechanical assist. It accepts sealants in both cartridge or 'sausage' forms, making it the most suitable tool for dozens of applications.

APPLICATIONS

Acrylic and elastomeric caulking as well as polyurethane sealants in 'sausage' form must necessarily be applied using DUROSEAL 600. Fill and seal construction expansion joints and joints in metal surfaces using this adaptable gun. Aluminum and wood frame sealing as well as ship-building applications cost less when using the versatile gun.

■ USE

A) 'Sausage': Unscrew the front cap, pull the piston back and insert the 'sausage'. Place the nozzle on the front cap, and screw it until a 'click' sound is heard. Use a razor blade or a knife to cut the nozzle on a slant. Cut the nozzle to the appropriate point that will yield the desired thickness of the sealant.

B) Cartridges: Remove from the piston the plastic washer by removing the threaded nut. Replace the nut to the piston and use the gun with the metal round, smaller diameter plate that fits into the bottom of the cartridge.

C) Cementitious: Unscrew the front cap, dip the gun into a bucket with clean water, pulling the piston up and down, at least two times to wet its interior. Then, use a flexible container to fill the barrel of DUROSEAL

600 with the desired cementitious product (as much needed to work for 30 minutes).

Cut the nozzle on a slant, to the appropriate point that will yield the desired thickness of the sealant. Screw the front cap together with the nozzle. After the application, clean the gun thoroughly with water.

REPLACEMENT NOZZLES are icluded with the tool and they are also available by DUROSTICK, for various applications.

■ NOTE

For epoxy resins, epoxy putties, glue in paste forms and generally any product that would be hard to remove from the gun, it is reccomended to use the BLANK CARTRIDGE of DUROSTICK. The cartridge is fully compatible with the versatile gun, DUROSEAL 600.

PACKAGING

Carton box with 12pcs.

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 10, GR: 570 22,

Tel: +30 2310 795 797, +30 2310 797 365,

Fax: +30 2310 797 367
Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.