# **GROUT SCRAPER**





### **■ PROPERTIES**

Extremely durable grout scraper with an ergonomic soft-grip handle. The product is suitable and necessary for easy grout removal. It features two hard blades, with the ability to remove one for narrower (smaller) joints. The ease of use makes it an indispensable tool for the complete or the partial removal of cementitious grouts.

## APPLICATIONS

DUROSTICK Grout Scraper quickly and easily removes worn out or dirty cementitious grouts. It then facilitates the grouts' renewal; cleanliness,

watertightness, and even the re-grouting process with cementitious or epoxy grouts.

#### USE

• Destroyed grout: Remove the existing cementitious grout to a depth from 3mm to 5mm to make before regrouting. Redefine, if need be, the final color of the grout. Select one of the three cementitious VITREOUS GROUTS (0-3mm, 1-10mm, 5-20mm) of DUROSTICK, the DUROGROUT FLEX 1-8mm, or the epoxy grout DUROPOXY that can be cleaned easily and quickly only with water.

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.

## **GROUT SCRAPER**



- Worn-out grout: Remove the existing cementitious grout to a depth from 2mm to 3mm before regrouting, in the same way as described above.
- Stained or discolored grout (usual floor grout occurrence): Quickly and easily, without the use of strong or caustic chemicals, clean (scrape) the grout surface (to a depth of 0.5mm at the most), wipe away and remove all dust and dirt. Use a wet sponge and clean the residue. Allow for the cleaned surface to dry. Once dry, apply D-16 HYDROSTOP, the waterproofing agent for grout joints, available in a convenient container with a nozzle for easy application. In this way the grout is 'rejuvenated', it recovers its original color(s) and retains its watertightness for a long time.

**DUROSTICK S.A.,** 

MANUFACTURING OF ADHESIVES.

**PAINTS & MORTARS** 

**ATHENS:** ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 10, GR: 570 22,

Tel: +30 2310 795 797, +30 2310 797 365,

Fax: +30 2310 797 367 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.