

ANTISLIP ADDITIVE POWDER



Antislip microspheres for addition to floor protection varnishes



■ PROPERTIES

An antislip high-performance product. Suitable to use as an additive with any type of one or two-component, water or solvent-based floor varnish. It is essential as a varnish additive when applying them on walkable surfaces and surfaces that will become wet, for both interior and exterior applications. Its addition ensures safe walk surfaces and minimizes the chance of an accident.

■ ADVANTAGES

- Easy to mix
- Integrates seamlessly, without alter the characteristics of the product
- Resistance to solvents and acids
- High mechanical and chemical strengths
- Provides anti-slip properties even when wet
- Compatible with all varnishes.

■ APPLICATIONS

ANTISLIP ADDITIVE POWDER is ideal as a varnish additive when applying them on floors, stairs,

corridors, ramps, pool perimeters (copings), for floor linings with microcement, natural stone slabs, and wherever is necessary to apply protective varnish. It is also recommended for use in parking lots (garages) and car washes, etc.

■ CONSUMPTION - USE

Follow the preparation steps of the substrate that are recommended for each varnish. The quantity of ANTISLIP ADDITIVE POWDER is calculated based on the roughness necessary to impart to the varnish, depending on the floor's exposure to rain or frequent washing. On highly absorbent surfaces, apply the first coat of the selected varnish, without the addition of ANTISLIP ADDITIVE POWDER. Its addition is recommended for the second coat, at a rate of 2% by weight of liquid for matte varnishes, 3% for satin, and 4% for gloss varnishes. Mix well before use to homogenize (integrate) the microspheres into the varnish. During application, it is recommended to mix frequently to achieve a smooth dispersion of the microspheres on the surface. Apply in one or more

ANTISLIP ADDITIVE POWDER



Antislip microspheres for addition to floor protection varnishes

coats, depending on the roughness necessary to impart on the coated surface. Follow the varnish application instructions on its packaging.

■ NOTE

For two-component varnishes, add the ANTISLIP ADDITIVE -POWDER to component A and mix. Add the mixture into component B and mix again.

■ CONSUMPTION

Use 2% to 4% by weight, depending on the desired roughness to be imparted to the varnish.

■ STORAGE

Store in dry places, avoiding extreme temperatures.

■ SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 12 pcs of 150gr each one

TECHNICAL SPECIFICATIONS

■ Form - Color	Dry powder of constant grain size - Semi-transparent
■ Moisture content	0%
■ Grain size	250-350µm
■ Bulk density	1.25±0.10kg/lt
■ Melting point of product	150°C-160°C

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367

Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.