

D-7**Natural stone cleaner****■ PROPERTIES**

A powerful cleaner that removes construction residues from natural stones, restoring their natural look.

It cleans in depth accumulated dirt, salts, mud rain, black spots, mold, as well as oil, coffee, rust and uncured paint stains.

It does not affect the natural look of stones and/or grouts. Its use is necessary prior to waterproofing and/or decorating a surface with varnish.

■ APPLICATIONS

D-7 is used on walls and floors lined with natural stones. Before use, it is recommended to test the cleaner on a small, unseen area, particularly for stones sensitive to powerful cleaners (e.g. limestone). It is recommended to use the product 28 days after grouting. Its use is necessary for removing construction residues, prior to the application of the waterproofing agents RENOLIT or DUROSTICK NANO PROOF CERAMIC DS-270.

It is also necessary before applying any DUROSTICK stone varnishes, such as D-72, D-12, VISTA, DECOFIN EPOXY SF or DECOFIN POLYURETHANE.

■ LIMITATION OF USE

Application of D-7 is not recommended for marble or artificial stones, and decorative bricks.

■ USE**1. Application preparation**

During application it is strongly recommended to use goggles and plastic gloves.

In interior applications, open doors and windows to prevent vapor accumulation.

Remove stainless steel utensils and protect stainless sinks, faucets, etc., with plastic sheeting.

For exterior applications, ensure that residue accumulations near planted areas are avoided, as there is a risk of harming them.

D-7**Natural stone cleaner****2. Application**

Apply D-7 on the surface undiluted and scrub using a stiff broom. Let the product act for 3-5 minutes. Finish the process by rinsing thoroughly with plenty of water.

■ CONSUMPTION

1lt/4-5m² of surface.

■ STORAGE

Store in shaded places, protected from frost for 36 months from production date.

■ SAFETY DIRECTIONS

The product is corrosive and irritant to the respiratory system. It is recommended to keep locked away from the reach of children and apply it in well ventilated areas.

Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 15 pcs of 1lt each one
5 lt, 20lt containers

TECHNICAL SPECIFICATIONS

■ Form - Color	Liquid - Transparent
■ Bulk density	1.05±0.05kg/lt
■ pH	0-1
■ Application temperature	From +5°C to +35°C
■ Scent	Lemon
■ Contains hydrochloric acid	

Permit No. by General Chemical State Laboratory
ELEFSIS 3093/2008

DUROSTICK S.A.,
MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367
Email: info@durostick.com