

DECOFIN AQUA



Acrylic waterborne matte finish varnish for styling vertical surfaces



■ PROPERTIES

Acrylic, waterborne clear varnish with a matte finish, suitable for interior applications. It spreads evenly without leaving brush marks; it dries quickly and applies with exceptional ease, just like ordinary waterborne varnishes. It highlights decorated surfaces while it remains clear. It gives surfaces depth without affecting their colors and uniqueness, does not yellow nor peel off. It protects surfaces from everyday use and allows for cleaning with mild household detergents. Odorless, water soluble product that is friendly to human and the environment.

■ APPLICATIONS

DECOFIN AQUA, a waterborne matte finish varnish protects **interior vertical surfaces** decorated with paints, microcement DS-250, DS-252 FLEX or DS-256 FLEX VELVET, microcement in paste form DS-258 DECO MICRO FLEX, decorative cement mortar DS-259 DECO MICRO RESIN, and the microcement paste DS-258 DECO MICRO FLEX.

It coats artistic creations with a clear, durable film, ensuring the durability and longevity of their unique appearance for many years to come.

■ USE

1. Substrate preparation

Apply DECOFIN AQUA on sound, clean, and dust free surfaces. All decorated surfaces must be completely dry before applying the varnish therefore it is recommended to apply it in any case at least 2 days after their creation. In low temperature and high humidity conditions or when working with particularly thick decorative styling coats, such as surfaces decorated with microcement, stucco, etc., the varnish application times are extended for up to 4 days.

2. Application

DECOFIN AQUA is applied in one to two coats, with a roller (for the whole surface) and a paintbrush (for the corner cuts), after the product has been mixed very well. It dries on the surface in about an hour. In case of applying a second coat, it is recommended to apply it 4 hours after the first coat (the referred times depend on the environmental conditions, temperature - humidity).

DECOFIN AQUA



Acrylic waterborne matte finish varnish for styling vertical surfaces

■ CLEANING

Clean all tools with water immediately after use, and if needed, with soap or detergent solution.

■ CONSUMPTION

1lt/12-13m² per coat, depending on the absorbency of the surface.

■ STORAGE

Store in the factory sealed containers, in places protected from frost, for 18 months from production date.

■ SAFETY DIRECTIONS

The product needs no hazard labeling based on current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

■ NOTE

In places with high moisture content, the use of the acrylic, -solvent-based varnish with matte finish, VISTA is recommended.

■ PACKAGING

Carton box with 12 pcs of 750ml each one

TECHNICAL SPECIFICATIONS

■ Form - Color	Liquid - White, becomes transparent when dry
■ Resin	Acrylic
■ Bulk density	1,00±0,05kg/l
■ Solids by weight	30-32 % w/w
■ Solids by volume	29-31 % w/v
■ pH	8.0±0.5
■ Gloss	Matte
■ Application temperature	From +5 °C to +35 °C
■ Dilution	A ready to use product. Do not dilute.
■ Drying time	Approximately one hour (touch dry), depending on the ambient conditions (humidity, temperature)
■ Recoating time	After 4 hours

V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EU (Directive 2004/42/CE) for the particular product (Class A/i: 'One-pack performance coatings' Type WB): 140gr/l (2010). The ready to use product contains maximum 75gr/l V.O.C.

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com