

DUROLIN 250



Methylcellulose adhesive for paper-based and vinyl wallpapers



■ PROPERTIES

High quality methylcellulose adhesive in powder form, for hanging paper-based and vinyl wallpapers to walls.

■ ADVANTAGES

- Easy dilution only with water
- High coverage
- Easy application
- Quick drying without staining
- Excellent tack and bonding strength
- Durable against moisture and temperature variations
- Durable against the alkalis of lime mortars, gypsum mortars, and cement mortars.

■ APPLICATIONS

DUROLIN 250 offers the ability to firmly hang all paper-based and vinyl wallpapers, as well polyester-backed wallpapers onto absorbent substrates.

Suitable for smooth, embossed or woven, but also fabric, and velvet wallpapers as well as posters.

■ USE

1. Surface preparation

Surfaces must be sound, evenly absorbent, dry, clean, free from oils, dust and loose materials, and also need to be perfectly flat. For uneven surfaces, it is recommended to smooth with either the ultrafine skim coat paste STUCOFIX-P or the spackling/patching paste POWDER COAT of DUROSTICK, depending on the surface imperfections. Wall surfaces painted with intense colors that might bleed through the wallpaper, must first be painted white. Bubbled up or peeled paints must be removed completely. The ambient humidity must be within the specified parameters given by the wallpaper manufacturer. If there is existing wallpaper on the surface, remove it with the appropriate wallpaper remover or warm water. It is necessary to first prime

DUROLIN 250



Methylcellulose adhesive for paper-based and vinyl wallpapers

all particularly absorbent substrates using the adhesive itself.

2. Application

Empty the bag into a clean container with cool water, according to the section 'DILUTION-CONSUMPTION', and mix well for 30 seconds. Mix again after 20-30 minutes. The glue is ready for use. Spread the adhesive evenly on the back of the wallpaper with a clean and soft brush, following the saturation time, according to the wallpaper manufacturer's instructions. Hang the wallpaper on the wall and press it with a plastic trowel, or another similar tool, from top to bottom and from the center to the edges to remove any excess. Clean any residues and spills immediately with clean water and a sponge or damp cloth.

■ CLEANING

Clean all tools and hands with lukewarm water after the application completion.

■ DILUTION - CONSUMPTION

As primer: 200gr/8lt of water/60-80m².

Paper-based and vinyl wallpapers: 200gr/4.8lt of water/25-30m²/5-6 rolls*.

*Roll dimensions 10x0.53m.

■ STORAGE

Store in its factory sealed packaging in dry and cool places, for 48 months from production date.

■ SAFETY DIRECTIONS

The product needs no hazard labeling, based on current European and National legislation. However, it is recommended to keep away from the reach of -children. If swallowed, seek immediate medical advice and show the package or label.

■ NOTES

- Avoid applying the product to walls with rising damp. If there is a designated rising damp problem, it should be repaired with the cementitious

waterproofing mortar D-1 of DUROSTICK and allow for the product to dry thoroughly.

- Avoid using the product for hanging non-porous wallpapers on non-absorbent surfaces.
- Wallpapers in a roll packaging should be opened and spread well enough in advance before they are hung in order to 'straighten' them.

■ PACKAGING

Carton box with 12 bags of 200gr each one.

TECHNICAL SPECIFICATIONS

■ Composition - Form	Methylcellulose - Powder
■ Form - Color of mixed paste	Viscous paste - Clear
■ Paste pH	Neutral, almost pH 7-8
■ Solubility	30 minutes in cool water
■ Application temperature	From +10°C to +30°C and relative air humidity < 65%

DUROSTICK S.A.,
MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367
Email: info@durostick.com