

DUROWOOD



Acrylic waterborne wood putty



■ PROPERTIES

Water-soluble repair wood putty with high adhesion and zero shrinkage, that is odorless. It does not stain the wood surface. It dries quickly and resists moisture creating a hard, durable and smooth surface that can be sanded and drilled, planed down and lathed. Available in 15 selected, traditional wood colors. Optionally, it can be painted immediately after drying, with any type of enamel paint.

■ APPLICATIONS

DUROSTICK DUROWOOD is suitable for filling and covering imperfections on veneers, it seals gaps and joints on melamine as well as hardwood floors, lacquered surfaces, chipboard, Formica, MDF, etc. Ideal for woodworm repairs and wood furniture repairs, wood doors and ceiling panels. Suitable for interior and exterior use.

■ USE

All surfaces have to be clean, free of dust and oils. Apply the product in 1-2 coats, as is, using a small putty knife. Once dry, sand the putty down with the appropriate sandpaper. After use, close the container tightly. If the putty hardens, add a small amount of water and mix to restore it to its original condition.

■ NOTE

After applying the varnish, the color of wood putties gets highlighted.

■ CONSUMPTION

Depending on the application.

■ STORAGE

Store in places protected from frost, for 18 months from production date.

■ SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

■ PACKAGING

Carton box with 12pcs of 200gr each one

TECHNICAL SPECIFICATIONS

| | |
|------------------------------|--------------------------------|
| ■ Form - Color | Putty - Available in 15 colors |
| ■ Application temperature | From +8°C to +35°C |
| ■ Thinned/Diluted with water | |

DUROWOOD



Acrylic waterborne wood putty

Durowood Color chart of wood colors

| | | |
|---|---|---|
|  |  |  |
| MAPLE | SWEDISH | LIGHT PINE |
|  |  |  |
| OREGON | OAK | BEECH |
|  |  |  |
| TEAK | CHERRY | LIGHT WALNUT |
|  |  |  |
| DARK WALNUT | LIGHT MAHOGANY | DARK MAHOGANY |
|  |  |  |
| CHESTNUT | BLACK | WHITE |

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com