

HYDROSTOP PLASTER PRIMER



Preparation primer for colored plasters



■ PROPERTIES

Water-soluble acrylic micromolar primer, ideal for preparing surfaces to be coated with white or colored cementitious plasters.

It has high penetrating ability and it impregnates surfaces without creating a film. It effectively reduces surface absorbency while maintaining breathability. It ensures plaster protection from premature surface drying (early dehydration), eliminates the reduction of strength and the risk occurrence of cracks.

■ APPLICATIONS

Apply HYDROSTOP PLASTER PRIMER on highly porous substrates, such as base coat plasters and aircrete before applying white or colored plaster. It also ensures even drying and color uniformity across the entire surface of the new plaster.

■ USE

1. Surface preparation

Surfaces to be primed must be dry and free from dust, grease, pollutants etc.

2. Application

HYDROSTOP PLASTER PRIMER is diluted with water at a ratio of 1: 1, and applied by roller or spray.

Mix well before use. Allow for the primer to dry completely before applying the plaster.

■ CLEANING

Clean all tools with water, immediately after use.

■ CONSUMPTION

Approximately 10-12m²/lt, depending on the absorbency of the substrate and the dilution rate, on properly prepared surfaces.

■ STORAGE

Store in sealed containers and places protected from frost and intense solar radiation, for 24 months from production date.

■ SAFETY DIRECTIONS

The product needs no hazard labeling based on current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

■ PACKAGING

5lt, 20lt containers

HYDROSTOP

PLASTER PRIMER



Preparation primer for colored plasters

TECHNICAL SPECIFICATIONS

■ Form - Color	Emulsion - White, becomes transparent when dry
■ Bulk density	1.00±0.02kg/lt
■ pH	8.0±0.5
■ Drying time	3 hours at +20°C
■ Durable to Concrete carbonation and alkaline environments	

V.O.C. (Volatile Organic Compounds):

Limit value of maximum content of V.O.C.
per EU (Directive 2004/42/CE) for this product
(category A /h: 'binding primers', type WB): 30gr/lt (2010).
The ready to use product contains maximum 2gr/lt V.O.C.

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367

Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.