

HYDROSTOP SILICONE PRIMER



Bonding primer for plasters in paste form



■ PROPERTIES

Water-soluble, silicone-based, acrylic primer, suitable for silicone-based and acrylic plasters. It stabilizes and reduces the absorbency of surfaces resulting in the unbreakable adherence of all plasters in paste form.

■ APPLICATIONS

HYDROSTOP SILICONE PRIMER is ready to use on any porous surface, such as concrete and top coat plaster, gypsum and cement board. Designed to work with silicone and acrylic plasters, such as HYDROSTOP SILICONE PLASTER, HYDROSTOP ACRYLIC PLASTER and HYDROSTOP THERMO PLASTER of DUROSTICK.

■ USE

1. Surface preparation

The surface to be primed must be dry and free of dust, grease, pollutants, etc.

2. Application

Mix HYDROSTOP SILICONE PRIMER well and apply it undiluted. Coat the substrate evenly using a roller or a brush. Allow for the primer to dry for at least three hours and continue with the plaster application.

■ CONSUMPTION

Approximately 8-10m²/lt per coat, depending on the absorbency of the substrate.

■ STORAGE

Store in sealed containers and places protected from frost and intense solar radiation, for 24 months from production date.

■ SAFETY DIRECTIONS

The product needs no hazard labeling based on current European and National legislation.

HYDROSTOP

SILICONE PRIMER



Bonding primer for plasters in paste form

However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

■ PACKAGING

5lt, 20lt containers

TECHNICAL SPECIFICATIONS	
Form - Color	Emulsion - White, becomes transparent when dry
Bulk density	1.00±0.05kg/lt
pH	8±1
Drying time	3 hours at +20°C
Resistance	Resistance to concrete carbonation and alkalisne environment

V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EU (Directive 2004/42/CE) for this product (category A/n: "Bonding Primers", Type W): 30gr/l (2010). The ready to use product contains maximum 29gr/l V.O.C.

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com