

ROMIX PROFESSIONAL



Emulsion paint



■ PROPERTIES

Water dispersion, emulsion paint that is low odor. Economical, ideal for frequent paint maintenance, as it dries and repaints quickly, creating a uniform matte white surface. Distinguished for its remarkable adhesion and coverage. It allows the breathability of the substrate and it is easily applied. It offers a reliable and affordable solution for professionals and consumers alike. Ideal for spaces in need of frequent maintenance.

■ APPLICATIONS

ROMIX PROFESSIONAL is applied on new and existing interior spaces to be painted made of plaster, gypsum board, MDF, skimmed surfaces etc. Interior surfaces that require frequent painting and freshening up, such as large public projects, hotels, hospitals, gyms, schools, warehouses, etc. Suitable for painting surfaces such as walls, ceilings, stairwells, warehouses, etc.

■ USE

1. Substrate preparation

Concrete and marble-based plaster surfaces have to be dry, free from loose sections, and at least 30 days after their construction.

Surfaces soiled with soot and air pollution, are cleaned with the biodegradable cleaner BIOCLEAN (for nicotine and soot) or they are primed with METAL PRIMER of DUROSTICK.

For already painted, sound surfaces two coats with ROMIX PROFESSIONAL of DUROSTICK are enough.

For new marble-based plaster surfaces, sand them down using #60 sandpaper and prime using PVA PRIMER or 100% ACRYLIC PRIMER or the micromolar primer AQUAFIX of DUROSTICK.

Surfaces infested with black or green mold or even active fungi, necessarily have to be cleaned using DUROSTICK D-95 CLEANER, rinse thoroughly, dry and prime using SOLVENT BASED PRIMER or the micromolar stabilizer AQUAFIX of DUROSTICK.

ROMIX PROFESSIONAL



Emulsion paint

For skimming or spackling, apply STUCOFIX putty, STUCOFIX-P, POWDER COAT, GRANULAR ULTRA or GRANULAR of DUROSTICK, or any combination of the above, depending on the surface imperfections and smoothness of the finish required. Follow by priming the surfaces.

For already painted, sound surfaces 2 coatings with the DUROSTICK color of your choice are enough.

Surfaces soiled with soot and air pollution, are cleaned with the biodegradable cleaner BIOCLEAN (for nicotine and soot) or they are primed with METAL PRIMER of DUROSTICK.

For peeling surfaces, remove all loose materials and prime using 100% ACRYLIC PRIMER, or the micromolar stabilizer AQUAFIX of DUROSTICK.

Marble-based plaster surfaces with severe cracks, are sealed with fast setting repair plaster D-32 or the flexible, multipurpose mortar MEGAFIX of DUROSTICK and primed afterwards as described before.

Fill the joints around door and window casings, by using the paintable ACRYLIC CAULK for interior use, the elastomeric sealant DUROFLEX-PU of DUROSTICK for exterior use, or use interior/exterior versatile sealant and adhesive, DS POLYMER.

2. Application

Dilute ROMIX PROFESSIONAL with water at a ratio of up to 5%, depending on the substrate, and mix well. Apply with brush, roller or airless spray gun in 2-3 coats. Apply each additional coat, after the previous one is completely dry.

■ CLEANING

Clean all tools with water and detergent solution, immediately after use.

■ COVERAGE

Approximately 9-12m²/lt per coat, depending on the texture, the absorbency of the surface and the application method.

■ STORAGE

Store in places protected from sunlight and frost, for 18 months from production date.

■ NOTE

If needed, it is recommended to clean the freshly painted surface that ROMIX PROFESSIONAL was used, with a soft sponge and mild detergent, 20 days after its application.

■ SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

■ PACKAGING

Carton box with 12pcs of 750ml each one
3lt container (on a 120pcs pallet)
9lt container (on a 48pcs pallet)

ROMIX PROFESSIONAL



Emulsion paint

TECHNICAL SPECIFICATIONS	
■ Color	White that does not yellow over time
■ Colors	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors. The PAL base is colored via the COLOR COLLECTION System in any desired color.
■ Washability	> 10.000 cycles (per DIN 53778)
■ Gloss	Matte
■ Drying time	1 hour (touch dry), depending on the ambient conditions
■ Recoating time	4-5 hours, depending on the ambient conditions
■ Application temperature	From +8°C to +35°C

V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EU Directive 2004/42/CE for the particular product (Class A/a: 'Matte coatings for interior walls and ceilings' Type WB): 30gr/l (2010). The ready to use product contains maximum 29gr/l V.O.C.

DUROSTICK S.A.,
MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367
Email: info@durostick.com