

THINNER 201



Thinner for epoxy systems



■ PROPERTIES

Special purpose thinner for epoxy systems, consisting of glycols and a mixture of aromatic hydrocarbons.

■ APPLICATIONS

DUROSTICK THINNER 201 is used primarily for thinning the two-component epoxy paint DUROEPOXY, the two-component epoxy primer DUROEPOXY PRIMER and the ALUMINUM & GALVANISED PRIMER of DUROSTICK. Use it to clean metal structures and constructs, after their sanding. Clean them from oils and rust residues. Use it also to clean the epoxy system application tools and equipment.

■ USE

Add DUROSTICK THINNER 201 at a ratio of 1-5% in DUROEPOXY PRIMER and 5-10% in DUROEPOXY of DUROSTICK, always following the recommended dilution rate and use instructions on each product's packaging.

■ CONSUMPTION

1-5% in DUROEPOXY PRIMER and 5-10% in DUROEPOXY.

■ STORAGE

Store in places protected from high temperatures and direct exposure to sunlight, for 12 months from production date.

■ SAFETY DIRECTIONS

The product is classified as highly flammable and harmful.

It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 15pcs of 1lt each one

THINNER 201



Thinner for epoxy systems

TECHNICAL SPECIFICATIONS

■ Form - Color	Liquid - Transparent
■ Density	0.90±0.05kg/lt
■ Application temperature	From + 5°C to +35°C

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367

Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.