

DUROSTICK 100% ACRYLIC PRIMER



PROPERTIES

Water soluble acrylic primer for emulsion and acrylic paints. It offers strong adhesion and presents high resistance to alkaline surfaces. Stabilizes new surfaces to be painted and reduces their absorption capacity; thus increases the efficiency of the paints and doubles their life span. The primed surface ensures the color uniformity of the final coat. Odorless, high performance, dries quickly and penetrates deeply.

APPLICATIONS

DUROSTICK 100% ACRYLIC PRIMER it is recommended to be used prior to painting, on plastered and concrete wall surfaces, as well as surfaces coated with cementitious pastes (levelling fillers). Remove any loose paints from surfaces already coated with emulsion and acrylic paints and prime them with a single coat of 100% ACRYLIC PRIMER, before repainting. Suitable for any interior and exterior application.

USE

1. Surface preparation

All surfaces to be primed have to be clean, dry, and free from loose paints, dust, and formwork oils. Absorbent surfaces have to be primed with one part 100% ACRYLIC PRIMER and two parts water. On low absorption surfaces, the mixing ratio has to be 1:3, to avoid the creation of a glossy film.

2. Application

The diluted product must be stirred well before application and periodically, to avoid separation of ingredients. Apply it with a roller, brush or airless spray gun.

CLEANING

Clean all tools with water and detergent solution immediately after use.

PERFORMANCE

Approximately 10-15m²/lt, depending on the absorbency and dilution, on properly prepared surfaces.

DUROSTICK 100% ACRYLIC PRIMER



STORAGE

Store in places protected from frost, for at least 18 months from production date.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

Carton box with 12 pcs of 750ml each one 3lt, 10lt containers

TECHNICAL SPECIFICATIONS	
Form - Color	Concentrated acrylic emulsion -White, becomes transparent when dry
Density	1.00±0.03kg/lt
Application temperature	From +5°C to +35°C
Drying time	1 hour (touch dry), at 25°C
Paintable	After 4-6 hours, depending on the ambient conditions
Odorless, human and environmet friendly	
V.O.C. (Volatile Organic Compounds): <i>Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/h: 'Binding primers' Type WB): 30gr/lt (2010). The ready to use product contains maximum 14gr/lt V.O.C.</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com