

DUROSTICK 10 YEARS WARRANTY



100% Acrylic paint



PROPERTIES

Top quality acrylic paint that is resistant to moisture and frost, intense sunlight, environmental pollution and alkalis. It allows for the breathability of surfaces, being at the same time water vapour permeable. It creates a carbonation barrier on exposed concrete surfaces and does not saponify. It has good workability, strong adhesion, unique coverage and high efficiency. It is distinguished for its exceptional whiteness, but also for the stability of its shades. Gives the feeling of freshly painted, many years after its application. Certified 'cool' (*) paint (low thermal conductivity), with high reflectivity, certified by University of Athens, Department of Physics, Application Physics Division, as 100% acrylic paint for exterior wall surfaces.

APPLICATIONS

DUROSTICK 10 YEARS WARRANTY is ideal for any kind of new or already painted exterior surface of plaster, concrete, cement board, etc.,

even in buildings by the sea. It is also exceptional for all interior surfaces made of concrete, and plaster, gypsum board, etc. Use it for any interior spaces that require frequent cleaning of its surfaces, e.g. children rooms, areas exposed to nicotine and tar, public and private offices, hospital areas, catering places etc.

USE

1. Surface preparation

Concrete and marble based plaster must be dry and free from loose materials and oils. At least 30 days must have passed from their construction completion

2. Application

Dilute DUROSTICK 10 YEARS WARRANTY with water at a ratio of 5-10%, depending on the substrate, and mix well. Both DARK and TRANSPARENT bases are diluted with water at a ratio of 2-5%. Apply with brush, roller or airless spray gun in 2 coats. Apply the second coat, after the first one has fully dried.

DUROSTICK 10 YEARS WARRANTY



100% Acrylic paint

(*) In order to comply with the parameters that characterize a paint as "Cool" material and to maximize its energy efficient benefits, by mainly maintaining its reflectivity, it is recommended to choose/apply a white or light color pain.

CLEANING

Clean all tools with water and detergent solution, immediately after use.

PERFORMANCE

Approximately 10-12m²/lt per coat, depending on the texture, the absorbency of the surface and the application method.

STORAGE

Store in places protected from sunlight and frost, for at least 18 months from production date.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

LIMITATION OF USE

Do not apply with temperatures below +8°C or if there is a chance of rain or frost within the next 12 hours

PACKAGING

Carton box with 12 pcs of 750ml each one
3lt container (on a 120 pcs pallet)
10lt container (on a 48 pcs pallet)

TECHNICAL SPECIFICATIONS

Color	White that does not yellow over time
Shades	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors. The Pal, Dark and Transparent bases are colored via the COLOR COLLECTION System in any desired color.
Washability	> 22,000 cycles (per DIN 53778)
Gloss	Matte
Drying time	1 hour (touch dry), depending on the ambient conditions
Recoating time	4-5 hours, depending on the ambient conditions
Application temperature	From +8°C to +35°C
Flammable	No
V.O.C. (Volatile Organic Compounds): <i>Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/c: 'Coatings for exterior walls of mineral substrate' Type WB): 40gr/lit (2010). The ready to use product contains maximum 39gr/lit V.O.C.</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com