

DUROSTICK ALUMINIUM CLEANER



Cleaning agent for aluminum surfaces



PROPERTIES

Powerful active cleaning agent. With just one spray, it easily removes pollutants from exhaust gases, salts, dirt, mud rain, and fresh emulsion paint splashes (2-3 days old at the most).

APPLICATIONS

DUROSTICK Aluminum CLEANER is ideal for use on unpainted, anodized or powder coated aluminum frames, without altering or affecting their original color.

USE

It is recommended, purely preventable, to apply the cleaner on a hidden spot of the surface to be cleaned, so as to determine its color stability, before continuing with the actual application. Subsequently, spray the aluminum parts that require cleaning and scrub lightly with a soft, cotton cloth or sponge. Allow the product to act for 1-2 minutes and rinse with clean water and a sponge. Dry the clean surfaces with a cotton cloth.

STORAGE

Store in shaded places, protected from sunlight and frost, for at least 36 months from production date.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed seek immediate medical advice and show the container or label.

PACKAGING

Paper box with 12 pcs of 500ml each one

DUROSTICK ALUMINIUM CLEANER



Cleaning agent for aluminum surfaces

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
Density	1.00±0.05kg/lt
pH	9.00±1.00
Flammable	No
Contains	Phosphates less than 5%, anionic surfactants less than 5%
<i>General Chemical State Laboratory Reg. No. 17705/0/2014</i>	
<i>Permit No. by General Chemical State Laboratory ELEFSIS: 3093/2008</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:
+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55
98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30
2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.