

DUROSTICK BATHROOM & KITCHEN



Fungi and mold resistant acrylic paint



PROPERTIES

Highly durable acrylic paint with long lasting protective action. Due to the special fungicidal components contained within its formula, it can protect the film of paint created on the surface as it does not promote nor support mold creation or fungi growth. Suitable to be applied in spaces with intense moisture, and condensations. It is also essential in places with poor ventilation, and lack of natural light. It has great workability, applies with ease, powerful adhesion and dries quickly. Distinguished for its remarkable stain coverage, high efficiency and performance. Its properties and abilities make it the ultimate solution for spaces with permanent moisture.

APPLICATIONS

DUROSTICK BATHROOM & KITCHEN is highly effectively in spaces such as kitchens, bathrooms, warehouses, basements, as well as the surrounding spaces of heated pools, ceilings

with poor thermal insulation etc. Apply it on plaster, concrete, gypsum boards, plastered walls and ceilings.

USE

1. Substrate preparation

Concrete and marble surfaces must be dry and smooth, free of loose materials, oils, mold, salts, dust and at least 30 days have passed after construction.

Surfaces infested with black or green mold or even active fungi, necessarily have to be cleaned using DUROSTICK D-95 CLEANER, rinse thoroughly, dry and prime using SOLVENT BASED PRIMER or the micromolar stabilizer AQUAFIX of DUROSTICK.

2. Application

Dilute DUROSTICK BATHROOM & KITCHEN with water at a ratio of 5-10%, depending on the substrate, and stir well. Apply with brush, roller or airless spray gun in 2 coats. Apply the second coat, after the first one is completely dry.

DUROSTICK BATHROOM & KITCHEN



Fungi and mold resistant acrylic paint

CLEANING

Clean all tools with water and detergent solution, immediately after use.

PERFORMANCE

Approximately 11-13m²/lt per coat, depending on the texture, the absorbency of the surface and the application method.

STORAGE

Store in places protected from sunlight and frost, for at least 18 months from production date.

NOTE

If needed, it is recommended to clean the freshly painted surface that DUROSTICK BATHROOM & KITCHEN was used, with a soft sponge and mild detergent, 15 days after its application.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

Carton box with 12 pcs of 750ml each one
3lt container (on a 120 pcs pallet)
10lt container (on a 48 pcs pallet)

TECHNICAL SPECIFICATIONS

Color	White that does not yellow over time
Shades	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors.
Washability	> 20,000 cycles (per DIN 53778)
Gloss	Matte
Drying time	1 hour (touch dry), depending on the ambient conditions
Recoating time	4-5 hours, depending on the ambient conditions
Application temperature	From +8°C to +35°C
Flammable	No
V.O.C. (Volatile Organic Compounds): <i>Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/a: 'Matte coatings for interior walls and ceilings' Type WB): 30gr/lt (2010). The ready to use product contains maximum 29gr/lt V.O.C.</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367
E-mail: info@durostick.com