

# BIOCLEAN INDUSTRIAL



Biodegradable cleaner - removes oils, grease and mineral oils



## PROPERTIES

Biodegradable cleaner without ammonia, phosphates, and petroleum products per the European directive EC 648/2004 governing detergents in terms of their biodegradability.

## APPLICATIONS

BIOCLEAN industrial removes grease, petroleum and oils from walls and floors, machines, engines etc. Its high strength formula makes it essential for shipyards, aluminum and steel manufacturing industries, garages, car wash facilities, gas station, ship decks, public transportation vehicles etc. Dissolves and removes formwork oils that is the primary cause for the failed adhesion of plasters and paints. Necessary after the use of metal formworks. It easily breaks down burnt grease in ovens and grills without leaving any residues.

## USE

Spray the areas you want to clean and wait for a few minutes. Rinse with water. The resulting

waste degrades safely, without accumulations. For milder cleaning action, if needed, dilute the product with water in a ratio of 1: 1 up to 1:5. For grease and industrial oil stains, use the product undiluted. It can be used in combination with a cleaning machine.

## CONSUMPTION

1lt/12-14m<sup>2</sup> of surface.

## STORAGE

Store in places protected from frost, for at least 36 months from production date.

## SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

## PACKAGING

- Carton box with 12 pcs of 750ml each one

# BIOCLEAN INDUSTRIAL



Biodegradable cleaner - removes oils, grease and mineral oils

- 5lt, 20lt containers
- 1,000lt tank (special order)

## TECHNICAL SPECIFICATIONS

**Form - Color** Liquid - Mild cleaner - Green

**Density** 1.00±0.05kg/lit

**Scent** Long-lasting fresh scent

### Does not release vapours

**Contains** Non-ionic surfactants are less than 5%  
Anionic surfactants are less than 5%

The product has been officially examined and certified by the following German institutes:

- **FRESENIUS Institute**
- **BREGAU Institute for applied environmental technology**

## DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:

+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55

98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30

2310 797 365, Fax: +30 2310 797 367

E-mail: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.