

6.2 Styles

CERA VIVERE Natural wax sealer for decorative styling stuccos

PROPERTIES

Waterborne emulsion, based on high quality natural wax, suitable for interior use. It provides unique protection and durability on any decorative styling stuccos and pastes it is applied on. It contains special additives that 'give' luster to surfaces, highlighting their style and texture. It thus creates an excellent finishing touch with splashes of color, making them (the surfaces) comparable to the magnificent feel and aesthetic of real marble ones.

It showcases the decorated surfaces, adding depth, without affecting their color tones. Due to its special composition, it allows for the breathability of all surfaces it is applied on and their easy cleaning with mild household cleaners. It applies evenly without dilution; it is easy to use and it dries in a couple of hours, depending on the ambient conditions. It is an odorless, waterborne product, friendly to human and the environment.

APPLICATIONS

CERA VIVERE is ideal for decorative styling stuccos applied on walls, either in

paste form like STUCCO VIVERE (pic.2), also cement based stuccos, like MATIZ Stucco Decorativo (pic.1) of DUROSTICK.

USE

1. Surface preparation

Surfaces must be clean, free from dust; oils, oils, and have to be thoroughly dry.

2. Application

The decorative styling stuccos' surfaces have to be cured for 2 to 4 days, depending on the ambient conditions (temperature and humidity), in order to apply the wax, in one and up to two coats. No dilution is necessary.

It is applied with a cotton cloth, decorative styling glove, or with a low rpm power polisher.

Twenty to thirty five minutes after application (allowing the surface to dry up), polish the surface with a cotton cloth or a power polisher. If the range of speed selection of the device is from 1-10, set it to positions between 5-7.

CLEANING

Clean all tools with water, immediately after use, and if needed, with soap or detergent solution.



pic. 1



pic. 2

TECHNICAL SPECIFICATIONS

Form - Color	Liquid - Off yellow
Chemical base	Water based wax emulsion
Density	1.00 ± 0.05 kg/lt
Solids by weight	34 - 35 % w/w
pH	9.0 ± 1.0
Gloss	Gloss
Application temperature	From +5 °C to +35 °C
Dilution	The product is ready to use. Do not dilute.
Drying time	Approximately one hour (touch dry), depending on the ambient conditions (humidity, temperature)
Friendly to human and the environment	

V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A1b: 'Glossy coatings for interior walls and ceilings' Type WB): 100 gr/lt (2010). Ready to use product contains maximum 2 gr/lt V.O.C.

CONSUMPTION

1lt/12-13m² per coat, depending on the surface absorbency.

STORAGE

Store in the factory sealed packaging in spaces protected from frost, for at least 18 months from production date.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

Carton box with 12 pcs of 750ml each one