

DUROSTICK D-15



Cesspool and sewer cleaner



PROPERTIES

Very powerful cleaner for cesspools and sewers. Use it without dilution. Deposits such as grease and soap scum lead to pipe scaling that results in clogging. The cleaner works on the pipe walls of the sewer system, dissolving all accumulations. D-15 cleaner is heavier than water and flows through it, easily reaching to where solidified fats and scum close the pores of the walls of the cesspool. It effectively breaks down the fats and scum, opening the pores of the walls. The wastewater is now free to drain through the newly opened pores of the cesspool walls. The avoidance of the cesspool overflow, the unpleasant odors and the necessity for frequent evacuations leads to savings.

APPLICATIONS

D-15 is used to clean sewer pipes and to open the pores of cesspool walls. Suitable for absorbent and septic tanks. Empty it either into the piping system or directly into the tank.

USE

For cesspool cleaning, use 5kg per 8m³ of wastewater. After five days, the cleaner will open the pores and the wastewater level will be reduced. Tanks or cesspools that have not been recently cleaned, may need a second dose. For maintenance, empty 2kg of D-15 for every 8m³ of the cesspool, every six months. Clean the sewer system by emptying 2kg at the beginning of the network and repeating after 5 days.

CONSUMPTION

600-800gr/m³, depending on the use.

STORAGE

Store in shaded places away from any heat source, for at least 24 months from production date.

SAFETY DIRECTIONS

The product is classified as flammable and toxic. It is recommended to keep away from the reach of children and apply it in well ventilated areas.

DUROSTICK D-15



Cesspool and sewer cleaner

Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

PACKAGING

Carton box with 6 pcs of 5kg each one

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
Density	1.14±0.05kg/lit
Dinstinctive odor	Yes
Water soluble	No
<i>General Chemical State Laboratory Reg. No. 5310/0/99</i>	
<i>Permit No. by General Chemical State Laboratory ELEFSIS: 3093/2008</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:

+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55

98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30

2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.