



DECLARATION OF PERFORMANCE

DoP [EN] No. 018 DURO-CPR-7-2013



1. Unique identification code of product-type:
DUROSTICK D - 23 marble and granite adhesive
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
The coding shown on the packaging is the production date of the product.
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
Reinforced tile adhesive with minimal slip C2T for installing marble and granite.
4. Name, register name or register trade mark and contact address for the manufacturer as required to Article 11:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE
5. Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:
Not applicable.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3.
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 12004: 2007+A1: 2012 - EN 12004: 2007+A1: 2012
The notified control laboratory MIRTEC with number NB 0437 has carried out tests to determine the product type under system 3 and issued a test report No. 3675.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable.
9. Declared performance:

Essential characteristics	Declared performance	Harmonized Technical specification	
Reaction to fire	Euroclass (A1/A1 _{fl})		EN12004: 2007+A1: 2012
Bond strength as:		EN 1348 8.2	
Tensile adhesion strength	>1.0N/mm ²		
Durability for:			
Tensile adhesion strength after heat ageing	>1.0N/mm ²	EN 1348 8.4	
Tensile adhesion strength after water immersion	>1.0N/mm ²	EN 1348 8.3	
Tensile adhesion strength after freeze-thaw cycle	>1.0N/mm ²	EN 1348 8.5	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Evdoxia Kafritsa



Aspropyrgos 11/07/2013

R&D Manager, QC mortars lab



**DUROSTICK S.A
ASPROPYRGOS ATHENS PC: 19300
GREECE
06**

EN 12004: 2007+ A1: 2012

**DUROSTICK D-23
DoP No. : 018
C2T**

**Enhanced adhesive with reduced slip
Interior exterior use**

**Reaction to fire: Euroclass A1
Release of dangerous substances: see MSDS**

**Bond strength as:
-Tensile adhesion strength: $\geq 1.0 \text{ N/mm}^2$**

**Durability for:
-Tensile adhesion strength
after heat ageing: $\geq 1.0 \text{ N/mm}^2$**

**-Tensile adhesion strength
after water immersion: $\geq 1.0 \text{ N/mm}^2$**

**-Tensile adhesion strength
after water immersion: $\geq 1.0 \text{ N/mm}^2$**