

# DUROSTICK D-25



Self polishing liquid for marble, honed granite & cotto flooring



## PROPERTIES

Self polishing liquid, based on wax and special polymers. It offers excellent luster and protection for existing or new marble, honed granite and cotto. Its application will also highlight the natural beauty and aesthetic value of any marble and granite. It creates a clear protective membrane, it is slip resistant, antistatic and it has a pleasant scent.

## APPLICATIONS

DUROSTICK D-25 is highly recommended for existing marble flooring and mosaic, because it restores their lost luster and shine (pic.1). Suitable both indoors and out, as well as for building facades, monuments, statues etc.

## USE

### Surface preparation

Clean all dull, unpolished existing marble surfaces using DUROSTICK D-21 cleaner. Rinse and dry the surfaces thoroughly and apply the waterproofing liquid, D-22 or NANO PROOF MARMO DS-275 of DUROSTICK. Allow for 24

hours to pass and protect the surfaces using the self polishing liquid D-25, by applying the product, as directed.

### Application

On a clean surface, apply it undiluted using a soft, lint-free cloth or soft sponge (pic. 2) until the product dries completely. Once dry, buff the surface lightly using a soft, dry cloth to give extra shine to the surface. To maintain the luster, one bottle cap of D-25 in the mopping water in sufficient, even when combined with other detergents.

## CONSUMPTION

1lt/8-12m<sup>2</sup>, depending on the surface.

## STORAGE

Store in shaded places protected from frost, for at least 36 months from production date.

## SAFETY DIRECTIONS

The product needs no hazard labeling, based on current European and national legislation. However, it is recommended to keep away from the

# DUROSTICK D-25



Self polishing liquid for marble, honed granite & cotto flooring

reach of children. If swallowed, seek medical advice and show the container or label. Before use, read the cautions on the product packaging or the Material Safety Data Sheet.

## PACKAGING

Carton box with 15 pcs. of 1lt each one 5lt container

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid, White, becomes transparent when dry
Density	1.00±0.05 kg/lt
pH	8-9
Application temperature	From +5°C to +35°C
Temperature resistance	From -30°C to +100°C
Drying time	1 hour
Foot traffic	After 3 hours
Environment Friendly	

## DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS  
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,  
 Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612  
 THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,  
 STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367  
 E-mail: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.