

DUROSTICK D-28



Self polishing liquid wax for wood floors



PROPERTIES

DUROSTICK D-28 is a self-polishing metal parquet, wax-based and special polymers, ideal for wooden floors. A water soluble product, it creates exceptional luster and protects all floor types, including hardwood and softwood floor surfaces, without affecting the wood color. Protects from scuff marks, scrubbing, light scratches and dirt, as well as time related weathering and the frequent use of detergents. Creates a transparent protective film that is anti-static, anti-slip and has a pleasant fragrance.

APPLICATIONS

Apply DUROSTICK D-28 periodically on every wood floor surface to provide it with moisturising care and lasting shine.

USE

1. Surface preparation

Remove all the dust and any stains thoroughly, preferably using BIOCLEAN biodegradable gen-

eral purpose cleaner that does not damage lacquered wood surfaces. Rinse the wood floor from the cleaning agent thoroughly and wait for it to dry completely.

2. Application

Apply it as is, without any dilution, evenly over the entire surface, using a soft, lint-free cloth or a soft sponge. Make sure that there is no excess product left on the surface after its application. Once dry, buff lightly with a dry, soft cloth to enhance luster and sheen. To maintain the surface luster and the protection the product provides, add 2-3 bottle caps into 4-5lt of water and mop the entire floor normally. Just make sure to wring the mop well and allow for the floor to dry thoroughly before any foot traffic begins.

LIMITATION OF USE

Its application is not recommended on floor surfaces previously coated with products containing oil or wax. Refrain from using the product on existing flooring surfaces that are severely worn out, damaged or without any sealer coat on

DUROSTICK D-28



Self polishing liquid wax for wood floors

them. If you are not sure about any of the above conditions, on a non-visible spot of the surface, test the product before proceeding with the application across the entire surface.

CONSUMPTION

1lt/8-12m² of surface.

STORAGE

Store in shaded places protected from frost, for at least 36 months from production date.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

PACKAGING

Carton box with 15 pcs of 1lt each one
3lt containers

TECHNICAL SPECIFICATIONS	
Form - Color	White, it becomes transparent when dry
Density	1.00 ± 0.05kg/lt
pH	8-9
Application temperature	From +5°C to + 35°C
Drying time	1 hour
Foot traffic	After 3 hours
Friendly to human and the environment	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:
 +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55
 98 350, Fax: +30 210 55 99 612
 THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30
 2310 797 365, Fax: +30 2310 797 367
 E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.