



DECLARATION OF PERFORMANCE

DoP [EN] No. 060 DURO-CPR-7-2013

- Unique identification code of product-type:
DUROSTICK D - 40
- Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
The coding shown on the packaging is the production date of the product.
- Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
**General purpose plaster for interior and exterior use.
Fiber reinforced base/scratch coat plaster GP: CSIV/W1**
- Name, register name or register trade mark and contact address for the manufacturer as required to Article 11:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE
- Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:
Not applicable.
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4.
- In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 998-2: 2010
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable.
- Declared performance:

Essential characteristics	Declared performance	Harmonized Technical specification
Reaction to fire	Euroclass A1	
Compression strength	CV IV>6.0N/mm ²	EN 1015-11
Capillary water absorption	W1<0.4kg/m ² .min ^{0.5}	EN 1015-18
Adhesion to concrete	≥0.50N/mm ²	EN 1015-12
Water vapour permeability	μ= 15/35	EN 1015-21
Thermal conductivity λ _{10, dry} P=50%	1.07	EN 1745: 2000 (tab, A12)

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Evdoxia Kafritsa

Aspropyrgos 11/07/2013

R&D Manager, QC mortars lab



**DUROSTICK S.A
ASPROPYRGOS ATHENS PC: 19300
GREECE
07**

EN 998-1:2010

**DUROSTICK D-40
DoP No. : 060**

**Fiber reinforced base coat plaster
GP: CSIV/W1**

Reaction to fire:	Class A1
Adhesive strength:	>0.50N/mm² FP: B
Water absorption:	W1
Water vapour diffusion coefficient:	$\mu = 15/35$
Thermal conductivity (λ_{10}, dry):	1.07 (P=50%)
Durability (against freeze-thaw):	Evaluation based

on provisions valid in the intended place of the mortar