

DUROSTICK D-72



Waterborne and odorless stone varnish



PROPERTIES

Acrylic, waterborne clear impregnation varnish for stone. It remains clear; it does not peel off nor yellow. It highlights the natural grain and veins of stone and creates a 'permanent wet' look on the surface. The varnish D-72 of DUROSTICK protects the lined floor grouting material from cracks, deterioration and dirt.

APPLICATIONS

DUROSTICK D-72 waterborne varnish can be applied where aesthetic requirements call for gloss or satin, and at the same time protected, interior surfaces. Waterborne, odorless, suitable for floors lined with natural stone, slate and stone slabs as well as artificial stone, decorative bricks, porous blocks and colored pebbles etc. Ideal for coating rocks of various shapes and sizes, highlighting their natural color, and at the same time providing protection against pollutants. If the desired look of the lining is a matte finish, then instead of using DUROSTICK D-72 it is highly recommended to use one of the following products, the matte impregnating waterproofer RENOLIT,

the matte water-based varnish DECOFIN AQUA, the matte solvent-based varnish VISTA or one of the matte polyurethanes based two component varnishes, DECOFIN AQUA PU and DECOFIN POLYURETHANE of DUROSTICK.

USE

1. Surface preparation

New surfaces have to be cleaned 3-4 weeks after grouting. Use a stiff brush and the stone cleaner, DUROSTICK D-7 to remove all construction residues. Clean existing surfaces from dirt, mud and emulsion paint residues in the same way as described above. Remove any enamel or varnish coatings using the corrosive cleaner, DUROSTICK D-26. Apply the varnish, at least, 24 hours after all other steps are completed and only when the surface is completely dry.

2. Application

D-72 is ready for use. Stir and apply on clean and dry surfaces with a varnish roller, a brush or a spray gun. Dilute only the first coat at a ratio of

DUROSTICK D-72



Waterborne and odorless stone varnish

1:1 with water, to achieve the maximum penetration and adhesion that is possible. Continue with one to two additional coats, with 2-3 hours difference between coats.

CLEANING

Clean all tools with warm water and soap, immediately after use.

CONSUMPTION

1lt/8-10m², depending on the absorbency of the surface.

STORAGE

Store in shaded places, protected from frost for at least 24 months from production date.

NOTE - LIMITATION OF USE

- Surface coated with the waterborne varnish for stone D-72, must not come in contact with water for at least the next 24 hours from its application.
- Not recommended for kitchen and bathroom applications.

SAFETY DIRECTIONS

The product needs no hazard labeling based on current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

- Carton box with 12 pcs of 750ml each one
- 2.5lt container

TECHNICAL SPECIFICATIONS

Form	Acrylic polyurethane dispersion product
Color	Off white, becomes transparent when dry
Density	1.05±0.05kg/lt
Solids by weight	34.0±1.0% w/w
pH	7.50±1.00
Application temperature	From +5°C to +35°C
Flammable	No
Gloss	1st coat: satin finish (dilute 1:1 with water) 2nd-3rd coat: gloss finish
Drying time	1 hour, depending on ambient conditions
Recoating time	2-3 hours

V.O.C. (Volatile Organic Compounds): Limit value of maximum content of V.O.C. per EC (Directive 2004/42 / EC) for this product (category A/b: "One-pack performance coatings", type WB): 140gr/lt (2010). The ready to use product contains maximum 10gr/lt V.O.C.

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612
 THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367
 E-mail: info@durostick.com