

DUROSTICK D-95 CLEANER



Mold & mildew remover



PROPERTIES

Powerful cleaner that is highly effective for the immediate removal of mold and mildew from interior and exterior surfaces. It removes mold and mildew, black spots, algae, moss, lichens and other microorganisms from spots and areas with moisture concentration. It sanitizes surfaces and leaves a pleasant scent.

APPLICATIONS

D-95 CLEANER offers its exceptional cleaning action in interior spaces with high moisture concentration such as bathrooms, kitchens, warehouses, cellars, cottages and vacation houses that remain unused for a long time. Its combined use with DUROSTICK WATERTRAP dehumidifier, offers the best possible protection against moisture for spaces used periodically. It is also ideal for spots and areas with high water vapour concentration, e.g. tile joints in bathtubs and sinks as well as showers. It can also be used on ceilings, in buildings not properly thermally insu-

lated, and in many more applications. Use it outdoors, under balconies, in flower boxes, on natural stone steps, on clay tile roofs, flat roofs prior to their waterproofing, and many other spaces. Rinse well, allow for the surface to completely dry and coat over it with paints and/or waterproofing products of DUROSTICK.

USE D-95 CLEANER is a highly drastic and exceptionally powerful cleaning agent. During application and rinsing, it is recommended to use protective gloves. Protect and/or cover, as needed, possible sensitive areas or plants, around the application surface. Spray from 20-25cm away, and allow for the product to act for approximately 10 minutes. Following, rinse with plenty of water. Repeat the procedure, in a highly unlikely situation that might be necessary.

CONSUMPTION

1lt/5-6m² of surface.

DUROSTICK D-95 CLEANER



Mold & mildew remover

STORAGE

Store in shaded places, protected from frost, for at least 18 months from production date.

SAFETY DIRECTIONS

The product is classified as corrosive. It is recommended to keep it locked, away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

PACKAGING

Carton box with 15 pcs of 500ml each one 5lt container

TECHNICAL SPECIFICATIONS	
Form - Clear	Liquid - Transparent
Density	1.00±0.05 kg/lt
Scent	Long-lasting fresh scent
pH	10-11.5
Flammable	No
It contains Chlorine-based bleaching agents 15% but less than 30%, non-ionic surfactants less than 5%.	
<i>General Chemical State Laboratory Reg. No. 8074/0/2003</i>	
<i>Permit No. by General Chemical State Laboratory ELEFSIS: 3093/2008</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:
+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55
98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30
2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com