

# DS-230



Adhesive fiberglass joint tape with 2x2mm mesh opening for drywall, cement board and cracks on concrete and plaster



## PROPERTIES

Alkali resistant fiberglass adhesive tape with mesh opening 2,5x2,5mm and weight 55gr/m<sup>2</sup>. Necessary for strengthening horizontal and vertical drywall and cement board joints.

## APPLICATIONS

Apply immediately following the first spackling coat using the drywall spackling material D-67 and coat over the tape with the second and final coat. Its application ensures resilient joints and prevents capillary cracks or bursting. Ideal for spot strengthening concrete cracks. It is suitable and necessary for at length applications of joints between floors and walls, before coating with cementitious waterproofing products.

## PACKAGING

Carton box

- 72 pcs. (roll 5cm x 20m)
- 24 pcs. (roll 5cm x 90m)

## TECHNICAL SPECIFICATIONS

<b>Form</b>	Alkali fiberglass mesh
<b>Color</b>	White

## DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MOR-TARS  
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612  
 THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367  
 Email: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.