

DUROSTICK DS-230



Adhesive fiberglass joint tape for gypsum board, cement board as well as cracks on concrete and plaster with 2.5x2.5mm mesh opening



PROPERTIES

Alkaline self-adhesive glass tape (gauze), with frame opening 2.5x2.5mm and weight 55gr/m². Necessary for strengthening horizontal and vertical gypsum and cement board joints.

APPLICATIONS

Apply immediately after the first coat during taping, when using the joint compound for gypsum board D-67. Cover the tape with the second and final coat. Its application ensures resilient joints and prevents capillary cracks or bursting. Ideal for spot strengthening cracks in concrete. It is suitable and necessary for at length applications of joints between floors and walls, before coating with cementitious waterproofing products.

PACKAGING

Carton box: 72 pcs (roll 5cm x 20m)
24 pcs (roll 5cm x 90m)

TECHNICAL SPECIFICATIONS

Form	Alkali resistant fiberglass mesh
Color	White

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367
E-mail: info@durostick.com