

DS-490



Reinforcing fiberglass mesh with 4x4mm mesh opening for cementitious brushable waterproofing mortars & spackling putties



PROPERTIES - APPLICATIONS

Fiberglass mesh with 4x4mm mesh opening and 90gr/m2 weight. It is necessary for integrated reinforcement of cementitious waterproofing coatings and resinous spackling putties for cement boards. Distinguished for its resistance to alkaline environments. Offers significant reinforcement of the spackling product(s) and prevents capillary cracks resulting from intense temperature variations.

Reinforces and bridges cementitious waterproofing coatings on balconies, roofs and pools as well as reservoirs and water towers.

PACKAGING

Roll 1m x 50m on a pallet with 48 pcs

TECHNICAL SPECIFICATIONS

Form	Alkali resistant fiberglass mesh
Color	White

DUROSTICK S.A., MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367

Email: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project