

DUROSTICK DS-490



Reinforcing fiberglass mesh for cementitious brushable waterproofing mortars and spackling pastes, with 4x4mm mesh



PROPERTIES - APPLICATIONS

Fiberglass mesh necessary for integrated reinforcement of cementitious waterproofing coatings and resinous spackling putties for cement boards. with 4x4mm mesh opening and 90gr/ m² weight. Distinguished for its resistance to alkaline environments. Offers significant reinforcement and prevents capillary cracks resulting from temperature variations. Reinforces and bridges cementitious waterproofing coatings on balconies, roofs and pools as well as reservoirs and water towers.

PACKAGING

Roll 1m x 50m on a pallet with 48 pcs

| TECHNICAL SPECIFICATIONS | |
|--------------------------|----------------------------------|
| Form | Alkali resistant fiberglass mesh |
| Color | White |

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612
 THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367
 E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.