



DECLARATION OF PERFORMANCE

DoP [EN] No. 096.DURO-CPR-9-2014

1. Unique identification code of product-type:
D U R O S T I C K D S - P O L Y M E R
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
The six-digit number printed on the package corresponds to the Batch Production Number of product.
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
Multipurpose elastomeric sealant & adhesive.
4. Name, register name or register trade mark and contact address for the manufacturer as required to Article 11:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE
5. Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:
Not applicable.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3.
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 15651 - 1
The notified testing laboratory Tecnia Research Innovation with No. 1292 conducted tests to determine the type of product under system 3 and issued a test report No. 14_06000-a.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable.
9. Declared performance:

PROCEDURE (IN ACCORDANCE WITH ISO 8340)

Essential Characteristics	Declared performance	Harmonized standard
Reaction to fire	Class E	
Release of Chemicals	None	See material safety data sheet
Water Tightness & Air Tightness as determined by :		
Resistance to flow	≤3mm	EN15651-1
Loss of volume	≤45%	EN15651-1
Determination of tensile properties after immersion in water (23°C)	≥25%	EN15651-1
Durability	Pass	EN15651-1


10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer

Dr. Aristidis Koutsibelis

Aspropyrgos 29/09/2014

R&D Manager, QA fluids lab

	
DUROSTICK S.A ASPROPYRGOS ATHENS PC: 19300 GREECE 14	
EN 15651-1 DS-POLYMER DoP No. :096	
Reaction to fire :	Class E
Release of Chemicals :	None
Resistance to flow:	≤3mm
Loss of volume:	≤45%
Determination of tensile properties after immersion in water (23°C):	≥ 25%
Durability:	Pass