

DUROLIN 200



Adhesive for paper-based wallpapers



PROPERTIES

High quality methylcellulose adhesive in powder form, paper-based wallpapers.

ADVANTAGES

- Fast – dissolving only with water
- High coverage
- Easy application
- Quick drying without staining
- Extreme wet tack wallpaper adhesive
- Durable against moisture and temperature variations
- Resistant to lime, plaster and cement mortar alkalis.

APPLICATIONS

DUROLIN 200 offers the ability to firmly adhere all paper-based wallpapers. It is also suitable for hanging posters. For vinyl-based and heavy wallpapers, it is recommended to use DUROLIN 300 of DUROSTICK.

USE

1. Surface preparation

Surfaces must be sound, evenly absorbent, dry, clean, free from dust, oils and loose materials, and also need to be perfectly flat. For uneven surfaces, it is recommended to either apply the ultrafine skim coat paste STUCOFIX-P or the spackling/patching paste POWDER COAT of DUROSTICK, depending on the surface imperfections. Wall surfaces coated with intense colors that might bleed through the wallpaper, must first be painted white. Bubbled up or peeled paints must be removed completely. The ambient humidity must be within the specified parameters given by the wall-paper manufacturer. If there is existing wallpaper on the surface, remove it with the appropriate wallpaper remover. On highly absorbent substrates, first prime using the same product following the appropriate dilution ratio, as indicated below.

2. Application

Empty the bag in a clean container with cool water, following the instructions on the 'DILUTION-CONSUMPTION' section, while mixing vigorously for 30 seconds. After 20-30 minutes, mix it again and it is ready for use. Apply the adhesive

DUROLIN 200



Adhesive for paper-based wallpapers

evenly to the back side of the wallpaper with a clean and soft (emulsion) brush. Follow the soaking time according to the wallpaper manufacturer's instructions. Place the wallpaper on the wall and press it with a roller from top to bottom and from the center to the edges to remove any excess adhesive. Clean any residues and spills immediately with clean water and a sponge or with a damp cloth.

NOTES

- Avoid applying the product to walls with rising damp. If there is a designated rising damp problem, it should be repaired with the cementitious waterproofing mortar D-1 of DUROSTICK and allow for the repair to dry thoroughly.
- Avoid using the product for hanging non-porous wallpapers on non-absorbent surfaces.
- Wallpapers in a roll packaging should be opened and spread well enough before they are hung in order to 'straighten' them.

CLEANING

Clean all tools and hands with lukewarm water after the application.

DILUTION - CONSUMPTION

As primer: 150gr/ 10lt of water/ 80m²

Lightweight wallpaper: 150gr/ 8lt of water/ 50m²/ 10 rolls*

Regular wallpaper: 150gr/ 7lt of water/ 40m²/ 8 rolls*

Heavyweight wallpaper: 150gr/ 6lt of water/ 30m²/ 6 rolls*

*Roll dimensions 10x0.53m

STORAGE

Store in its factory sealed packaging in dry and cool places.

SAFETY DIRECTIONS

The product needs no hazard labeling, based on current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the package or label.

PACKAGING

Carton box with 12 bags of 150gr each one

TECHNICAL SPECIFICATIONS

Composition - Form	Methylcellulose - Powder
Form - Color of mixed paste	Viscous paste - Clear
Paste pH	Neutral, almost pH 7-8
Dilution	30 minutes in cool water
Application temperature	From +10°C to +30°C and relative ambient humidity <65%

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612
 THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367
 Email: info@durostick.com