

DUROWOOD



Acrylic waterborne wood putty



PROPERTIES

Repair wood putty with high adhesion strength and zero shrinkage. It does not stain the wood surface. It dries quickly and resists moisture. It creates a hard, durable and smooth surface that can be sanded and drilled, planed down and milled. Odorless and water soluble. Available in 15 selected traditional wood colors. Optionally, it can be painted immediately after drying, with any type of enamel paint.

APPLICATIONS

Wood putty, DUROWOOD, is suitable for filling and covering imperfections on veneers, for sealing gaps and joints on melamine as well as hardwood floors. Exceptional also for lacquered surfaces, chipboard and Formica, MDF etc. Suitable for damage created by woodworm and repairs on wood furniture, wood doors and ceiling panels. Suitable for interior and exterior use

USE

All applicable surfaces have to be clean, free of dust and oils. Apply the product in 1-2 coats, as is, using a small putty knife. Once dry, sand the putty down with the appropriate sandpaper. After use, close the container tightly. If the putty hardens, add a small amount of water and mix to restore it to its original condition

NOTE

After applying the varnish, the color of wood putties gets highlighted.

CONSUMPTION

Depending on the application.

STORAGE

Store in places protected from frost, for at least 18 months from production date.

DUROWOOD



Acrylic waterborne wood putty

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

Carton box with 12 pcs of 200gr each one

TECHNICAL SPECIFICATIONS	
Form - Color	Putty - Available in 15 colors
Application temperature	From +8°C to +35°C
Thinned with water	
Friendly to human and the environment	



Any discrepancies between color samples and the final result are due to precision shortcomings in the printing process.

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:
 +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55
 98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30
 2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.