

DUROXYL Wood Protection/Conditioner



Paraciticide - eliminates woodworms



PROPERTIES

Effective, low odor insecticide for immediate action. It rids any type of wood constructs from wood eating insects or larvae and provides immediate, long lasting protection. It exterminates woodworm and stops the destruction of wood objects.

APPLICATION

DUROXYL Wood Protection/Conditioner, effectively treats, all infected by woodworm, wood structures such as window frames and doors, floors, furniture, pergolas etc., for both exterior and interior surfaces.

USE

Shake well before and during use. Unscrew the safety cap. Place the tip of the bottle into the hole of the wood surface that was created by the woodworm. Press the vial for approximately 5 seconds so the insecticide can reach to the invisible nesting area of the insect or larvae in order to exterminate it. After 24 hours, seal the

hole(s) with DUROWOOD , the acrylic, water-borne wood putty of DUROSTICK. In case woodworm appearance in timber store rooms, it is highly recommended to apply DUROXYL Wood Protection/Conditioner, (available in 2.5lt and 15lt containers), by brushing, spraying or dipping every piece of wood that is infected. Avoid using the product in hot or frosty conditions. Protect your hands with gloves and avoid any contact of the product with your face.

CONSUMPTION

Each 120ml vial can cure 1-2m² of wood surface, depending on the type and the absorbency of the treated wood.

STORAGE

Store in shaded places, away from any heat source, for up to 24 months from production date.

DUROXYL Wood Protection/Conditioner



Paraciticide - eliminates woodworms

SAFETY DIRECTIONS

The product is classified as harmful and flammable. It is recommended to keep away from the reach of children, and apply it in well ventilated areas. Before use, consult the precautionary information on the product label or in the Material Safety Data Sheet.

ATTENTION

It contains powerful insecticide, particularly harmful for any use other than the intended protection of wood.

KEEP AWAY FROM THE REACH OF CHILDREN.

PACKAGING

Paper box with 20 vials of 120ml each one

TECHNICAL SPECIFICATIONS	
Form - Color	Low viscosity liquid - Transparent
Density	0.80±0.05kg/lt
Solids by weight	6-10% w/w
Application temperature	From +5°C to +35°C
Drying time	1-2 hours (touch dry), depending on the application temperature
Dilution	Ready to use product. Does not dilute
Odor	Light, it becomes odorless when dry
V.O.C. (Volatile Organic Compounds): Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/f: 'Interior and exterior minimal build woodstains' Type SB): 700gr/lt (2010). The ready to use product contains maximum 675gr/lt V.O.C. Approval registration number: TP8-0125	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:

+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55

98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30

2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com