

DUROSTICK EXTRA



Highly durable emulsion paint



PROPERTIES

Emulsion paint of high whiteness and low odor during its application. It has strong adhesion, applies easily, and dries quickly. Provides excellent coverage, performance, and creates a uniform matte finish of exceptional durability. It does not saponify from frequent washing and its colors do not fade over time. It facilitates surface breathability, allowing water vapor to escape.

APPLICATIONS

DUROSTICK EXTRA is ideal for the protection and decoration of new and existing, painted surfaces made of plaster and concrete, brick, gypsum board spackled surfaces etc. Surfaces exposed to everyday and rough use such as hospitals and hotels, schools as well as children's rooms, etc.

USE

1. Substrate preparation

Surfaces from concrete and marble based plaster have to be dry, at least 30 days from their construction, and free from loose materials.

Surfaces soiled with soot and air pollution, are cleaned with the biodegradable cleaner BIO-CLEAN (for nicotine and soot) or they are primed with METAL PRIMER of DUROSTICK.

Already painted, sound surfaces two coats with DUROSTICK EXTRA are enough.

2. Application

DUROSTICK EXTRA with water at a ratio of 5-10%, depending on the substrate, and stir well. Both DARK and TRANSPARENT bases are diluted with water at a ratio of 2-5%. Apply with brush, roller or airless spray gun in 2 coats. Apply the second coat, after the first one is completely dry.

DUROSTICK EXTRA



Highly durable emulsion paint

CLEANING

Clean all tools with water and detergent solution, immediately after use.

PERFORMANCE

Approximately 11-13m²/lt per coat, depending on the texture, the absorbency of the surface and the application method.

STORAGE

Store in places protected from sunlight and frost, for at least 18 months from production date.

NOTE

If needed, it is recommended to clean the freshly painted surface that DUROSTICK EXTRA was used, with a soft sponge and mild detergent, 20 days after its application.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

LIMITATION OF USE

Do not apply if there is a chance of rain or frost within the next 12 hours.

PACKAGING

Carton box with 12 pcs of 750ml each one
3lt container (on a 120 pcs pallet)
10lt container (on a 48 pcs pallet)

TECHNICAL SPECIFICATIONS

Color	White, that does not yellow over time
Shades	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors. The PAL, DARK and TRANSPARENT bases are colored via the COLOR COLLECTION System in any desired color.
Washability	> 15,000 cycles (per DIN 53778)
Gloss	Matte
Drying time	1 hour (touch dry), depending on the ambient conditions
Recoating time	4-5 hours, depending on the ambient conditions
Application temperature	From +8°C to +35°C
Flammable	No
V.O.C. (Volatile Organic Compounds): <i>Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/c: 'Coatings for exterior walls of mineral substrate' Type WB): 40gr/lt (2010). The ready to use product contains maximum 39gr/lt V.O.C.</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367
E-mail: info@durostick.com