



# DECLARATION OF PERFORMANCE

DoP [EN] No. 009 DURO-CPR-7-2013

- Unique identification code of product-type:  
**EXTRA POWER tile adhesive.**
- Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):  
**The coding shown on the packaging is the production date of the product.**
- Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:  
**Enhanced adhesive with reduced slip and extended open time. Highly Deformable. C2TE/S2.**
- Name, registered name or registered trade mark and contact address for the manufacturer as required to Article 11(5):  
**DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE**
- Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:  
**Not applicable.**
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 3.**
- In case of the declaration of performance concerning a construction product covered by a harmonized standard:  
**EN 12004: 2007+ A1: 2012**  
The notified control laboratory ZUS with number NB 1020 has carried out initial tests to determine the product type under system 3 and issued a test report with number No. 1020-CPD-010028453 & 010-028692
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
**Not applicable.**
- Declared performance:

Essential characteristics	Declared performance	Harmonised standard Appropriate /Technical Documentation	
Reaction to fire:	<b>Euroclass (A1/A1<sub>f1</sub>)</b>		
Bond Strength as:	<b>&gt; 1N/mm<sup>2</sup></b>	EN 1348 8.2	<b>EN 12004:2007+A1:2012</b>
• Tensile adhesion strength			
Durability as:			
Tensile adhesion strength after:			
• heat ageing	<b>&gt; 1N/mm<sup>2</sup></b>	EN 1348 8.4	
• water immersion:	<b>&gt; 1N/mm<sup>2</sup></b>	EN 1348 8.3	
• freeze-thaw cycles:	<b>&gt; 1N/mm<sup>2</sup></b>	EN 1348 8.5	
Dangerous substances	<b>See MSDS</b>		

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer:**

Evdoxia Kafritsa

Aspropyrgos 12/12/2016

R&D Manager, QC mortars lab



**DUROSTICK S.A**

**ASPROPYRGOS ATHENS PC: 19300**

**GREECE**

**07**

**EN 12004:2007+ A1:2012**

**EXTRA POWER**

**DoP No.: 009**

**C2TE/S2**

**Enhanced adhesive with reduced slip and extended open time**

**Highly Deformable**

**Interior –exterior use**

- Reaction to fire: **Euroclass A<sub>1</sub>**
- Release of dangerous substances: **see MSDS**

**Bond Strength as:**

- Tensile adhesion strength : **≥1.00 N/mm<sup>2</sup>**

**Durability for:**

- Tensile adhesion strength  
after heat ageing: **≥1.00 N/mm<sup>2</sup>**
- Tensile adhesion strength  
after water immersion: **≥1.00 N/mm<sup>2</sup>**
- Tensile adhesion strength  
after freeze-thaw cycles: **≥1.00 N/mm<sup>2</sup>**