

GEL COAT CLEANER



Acid cleaning agent for polyester boats



PROPERTIES

Active and low foaming professional acid cleaning agent, suitable for removing any surface rust from the gel coat around various metal components and parts. It quickly removes yellow, brown and black stains from the waterline and the hulls of boats, restoring them to their original color(s).

APPLICATIONS

GEL COAT CLEANER is applied with the same success rate on any kind of surface (polyester, metal, and even fiberglass) that requires effective cleaning. Use it on boat hulls to easily remove hard sediment and microorganisms, salt stains, smudges, soot from exhaust pipes and other 'persistent' stains. Effectively removes rust from the rims of boat trailers.

USE

- During use and while rinsing, it is highly recommended to use protective goggles and plastic gloves.

- Shake well before use.
- Carefully empty the liquid into an open container and apply it with a paint brush.
- Allow for the cleaning agent to act for 10 minutes and rinse with a wet sponge or plenty of fresh water.
- On surfaces with 'tough' dirt and 'stubborn' stains, repeat the procedure.

CONSUMPTION

Depending on the application.

STORAGE

Store in places protected from sunlight and frost, for at least 18 months from production date.

SAFETY DIRECTIONS

The product is classified as corrosive. It is recommended to keep it locked away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

GEL COAT CLEANER



Acid cleaning agent for polyester boats

PACKAGING

Carton box with 12 pcs of 1lt each one
5lt containers (special order)

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
Density	1.30±0.05kg/lt
pH	0-1
Contains: More than 10% phosphoric acid, less than 5% non-ionic surfactants & less than 5% anionic surfactants among others.	
Permit No. By General Chemical State Laboratory ELEFSIS: 3093/2008	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:

+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55

98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30

2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.