



DECLARATION OF PERFORMANCE



No. 008 DURO-CPR-7-2013

- Unique identification code of the product-type:
DUROSTICK GOLD
- Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11:
The coding shown on the paperbags is the production date.
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer.
Enhanced deformable tile adhesive with reduced slip and extended open time C2TE/S1
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11:
DUROSTICK S.A. PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS PC.: 19300 GREECE
- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12:
Not applicable
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
- In case of the declaration of performance concerning a construction product covered by a harmonised standard:
EN 12004:2007+A1:2012

The laboratory ZUS, notified body NB 1020 determined the initial tests under system 3 and published test report No. 1020-CPD-010028453 & 010-028692

- In case of the declaration of performance concerning a construction product covered by a harmonised standard
Not applicable
- Declared performance

Essential characteristics	Declared performance	Harmonised standard Appropriate /Technical Documentation	
Reaction to fire:	Euroclass (A1/A1_{fl})		
Bond Strength as:	> 1N/mm²	EN 1348 8.2	EN 12004:2007+A1:2012
• Tensile adhesion strength			
Durability as:			
Tensile adhesion strength after:			
• heat ageing	> 1N/mm²	EN 1348 8.4	
• water immersion:	> 1N/mm²	EN 1348 8.3	
• freeze-thaw cycles:	> 1N/mm²	EN 1348 8.5	
Dangerous substances	See MSDS		

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Evdoxia Kafritsa

Aspropyrgos 11th July 2013

Head of Mortars Lab (QC, R&D)



**DUROSTICK S.A
ASPROPYRGOS ATHENS PC: 19300
GREECE
07**

EN 12004:2007+ A1:2012

**DUROSTICK GOLD
DoP No.: 008**

C2TE/S1

**Enhanced adhesive with reduced slip and extended open time
Deformable
Interior –exterior use**

- Reaction to fire: Euroclass A₁
- Release of dangerous substances: see MSDS

Bond Strength as:

- Tensile adhesion strength : $\geq 1.00 \text{ N/mm}^2$

Durability for:

- Tensile adhesion strength after heat ageing: $\geq 1.00 \text{ N/mm}^2$
- Tensile adhesion strength after water immersion: $\geq 1.00 \text{ N/mm}^2$
- Tensile adhesion strength after freeze-thaw cycles: $\geq 1.00 \text{ N/mm}^2$