



DECLARATION OF PERFORMANCE

No. 090 DURO-CPR-7-2013 : GRANULAR ULTRA

1. Unique identification code of the product:
090
2. Intended uses: **EN 998-1: General purpose rendering/plastering mortar.**
3. Manufacturer:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE, www.durostick.gr
4. Authorized representative:-
5. System of AVCP (assessment and verification of constancy of performance):
System 4
- 6a. Harmonized standard:
EN 998-1:2016

Notified body: -

- 6b. European Assessment Document **not applicable** European Technical Assessment **not applicable**
 Technical Assessment Body **not applicable** Notified Body **not applicable**

7. Declared performance

| Essential characteristics | Performance | Test method/ Harmonised Standard | |
|--|---|----------------------------------|----------------------|
| Reaction to fire | Euroclass A1 | EN 13501-1 | |
| Compressive strength | CS II :1.5- 5.0N/mm ² | EN 1015-11 | EN 998-1:2016 |
| Capillary water absorption | W0 : not specified | EN 1015-18 | |
| Adhesion | ≥ 0.50 N/mm ² | EN 1015-12 | |
| Water vapour permeability | μ 5/20 | EN 1015-21 | |
| Thermal conductivity λ _{10,dry} (P=50%) | 0.48 W/K·m | EN 1745-TabIA.12 | |
| Durability | evaluation based on provisions valid in the intended place of use of the mortar | EN 998-1:§5.3.2.2 | |


8. Appropriate Technical Documentation and/or Specific Technical Documentation: **Not applicable**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Evdoxia Kafritsa
 Function: Head of R&D, QC Mortars Dept.
 Place/Date: Aspropyrgos/ 3rd of September 2018

CE MARKING ACCORDING TO CPR 305/2011 AND EN 998-1:2016

| | |
|--|---------------------------------------|
|  | |
| DUROSTICK S.A ASPROPYRGOS ATHENS PC: 19300 GREECE 15 | |
| DoP No: 090 EN 998-1:2016 | |
| GRANULAR ULTRA General purpose plastering/rendering mortar GP: CSII/W0 | |
| Reaction to fire : | Euroclass A1 |
| Adhesive strength : | ≥0.50 N/mm² FP: B |
| Water absorption: | W0 |
| Water vapour diffusion coefficient: | μ 5/20 |
| Dry Bulk Density: | 1450 kg/m³ |
| Thermal conductivity (λ_{10, dry}): | 0.48 W/m·K (Table value P=50%) |
| Durability (against freeze/thaw): evaluation based on provisions valid in the intended place of use of the mortar | |
| Release of dangerous substances: see MSDS | |

The CE marking shown in this Declaration of Performance is the most recent, in accordance with the current regulation. Possible variations of the present marking with the corresponding one appearing on the packaging or the Technical Data Sheet may be due to the following reasons:

- *The packaging was already printed before the latest CE revision.*
- *Printing error*
- *Differences due to packaging sizes and printing method.*