

DUROSTICK GRANULAR ULTRA



Resin & fiber reinforced cementitious paste (for covering surface defects up to 15mm/coat)



PROPERTIES

White cementitious, fine grained polymer filler/paste with high coverage. Just add water to create an easy to use paste that does not shrink. Classified GP: CS II/W0 per EN 998-1.

ADVANTAGES

- When applied on concrete or plaster, it creates a ready to paint, smooth finish surface.
- High mechanical strengths.
- Highly resilient to moisture and adverse weather conditions.
- It does not require any improving additives or emulsions.
- High bonding strength on every construction surface, even on previously painted but sound surfaces.
- Quick and easy application.
- Exceptional filling ability, quick drying and easy to sand.
- Does not burst or 'sag' at thicknesses of up to 15mm per coat.
- Unique surface strength.
- Allows surface breathability.

APPLICATIONS

GRANULAR ULTRA of DUROSTICK is suitable and recommended for skimming all construction surfaces made of concrete, aircrete and plastered, or else, surfaces.

It covers every surface defect, even on painted walls and ceilings. Suitable to smooth, where necessary, masonries that have been coated with RELIEF or Mykonian plaster style. Suitable for interior and exterior surfaces.

USE

1. Surface preparation

To ensure proper adhesion of the product, surfaces have to be thoroughly cleaned and free from loose materials and dust. Any formwork oils that may exist have to be removed with the biodegradable oil cleaner, BIOCLEAN INDUSTRIAL. Avoid applying the product when the ambient or surface temperatures exceed 35°C. Soak thoroughly, especially exterior surfaces to ensure excellent adhesion conditions and eliminate the risk of early dehydration of the product, that could result in the reduction of its strength.

DUROSTICK GRANULAR ULTRA



Resin & fiber reinforced cementitious paste (for covering surface defects up to 15mm/coat)

2. Application

Empty 20kg of the mortar in a clean container with 5.8-6.0lt of water. Mix using a low-rpm drill, until a lump free, homogeneous paste is produced. Allow the mixture to mature for about 10 minutes and stir periodically without adding extra water. Apply using a large or smaller spackling/taping knife, a gauging trowel or a plastering/injection machine.

With one to two coats of 1-15mm each one, create a smooth surface that can be primed and painted. The surface can be sanded the very same day but it can also be smoothed with a wet plastering float when it is still fresh.

USEFUL TIPS - NOTES:

- The painting of GRANULAR ULTRA with the addition of pigments in powder form DUROCOLOR POWDER-C (in 96 shades of color chart), provides a unique ability to control the flatness of the walls and correct imperfections before painting. The resulting result eliminates the need for multiple coats of paint (especially in dark shades). In this way the cost of the application is significantly reduced due to the reduction of the quantity of paint and labor that in any other case would be necessary.
- Its high coverage per coat eliminates the need to plaster the surfaces, since it acts as a plaster, giving an extremely smooth finish. Smooth and even out plastered surfaces presenting technical flaws and defects, noticeably obvious when darker shades are applied on them, with excellent results.
- When looking for velvety surface indoors, skim coat the next day all the coated surfaces using the acrylic, ultrafine skimming paste, STUCOFIX-P of DUROSTICK.

CLEANING

Clean all tools with water immediately after use.

CONSUMPTION

Approximately 1.4kg/m²/mm thick coat.

STORAGE

Store in the factory sealed packages, in dry and shaded places for at least 12 months from production date.

SAFETY DIRECTIONS

The product contains Portland cement. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

NOTES

- Protect the product while it is still fresh from rain and frost.
- After hardening, the product is harmless to health and the environment.

PACKAGING

Paper bag of 20kg on 1,200kg pallet

DUROSTICK GRANULAR ULTRA



Resin & fiber reinforced cementitious paste (for covering surface defects up to 15mm/coat)

TECHNICAL SPECIFICATIONS (<i>Measurement conditions 20°C and 65% R.H.</i>)	
Form - Color	Cementitious mortar - White
Toxic	No
Bulk density of dry mortar	1.30±0.05kg/lt
Bulk density of fresh mortar	1.65±0.05kg/lt
Maximum grain size	0.60mm
Water requirement	5.8lt water in 20kg mortar/paste
Application temperature	From +5°C to +35°C
Temperature resistance	From -30°C to +80°C
Maximum application thickness	15mm/coat
Recoating time	After 4 hours
Pot life	At least 4 hours
PRODUCT PERFORMANCES	
Strength after 28 days, per EN 1015-11, to:	
• flexion	1.80±0.50 N/mm ²
• compression	4.30±1.00 N/mm ²
Strength after 28 days, per EN 1015-12:	
• adhesive	≥ 0.60 N/mm ²
Capillary water absorption (c) per EN 1015-18	0.90kg/m ² .min0,5
Water vapor diffusion coefficient per EN 1015-19	μ 5/20
Thermal conductivity λ _{10, dry} per EN 1745 (Table. A.12)	0.48 W/m.K
Reaction to fire per EN 13501-1	Euroclass A1



DUROSTICK S.A.
MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367
E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.