

5.3.1 Plastering products & plaster reinforcement

HYDROSTOP SILICONE PRIMER

Adhesion primer for plasters in paste form



TECHNICAL SPECIFICATIONS

Form - Color	Emulsion - White, becomes transparent when dry
Density	1.00±0.05kg/lt
Drying time	3 hours at 20°C
Resistance	Resistance to concrete carbonation and alkaline environment

Odorless, friendly to human and the environment

V.O.C. (Volatile Organic Compounds):

V.O.C. Limit of maximum V.O.C. content EC (Directive 2004/42/EC) for this product (category A/h: 'Binding primers' Type WB): 30gr/lt (2010). The ready to use product contains max 29gr/lt V.O.C.

STORAGE

Store in closed containers, in places protected from frost and strong sunlight, for at least 24 months from production date.

SAFETY DIRECTIONS

The product needs no hazard labeling based on current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

5lt, 20lt containers

PROPERTIES

Water soluble, silicone based, acrylic primer, suitable for silicone and acrylic plasters in paste form.

It stabilizes and reduces the absorbency of surfaces resulting in the unbreakable adherence of all based plasters in paste form.

APPLICATIONS

HYDROSTOP SILICONE PRIMER is ready to use on any porous surface, such as concrete and top coat plaster, drywall and cement board. Designed to work with silicone and acrylic plasters, such as HYDROSTOP SILICONE PLASTER and HYDROSTOP ACRYLIC PLASTER of DUROSTICK.

USE

1. Surface preparation

The surface to be primed must be dry and free of dust, oils, pollutants etc.

2. Application

Stir HYDROSTOP SILICONE PRIMER well and apply it undiluted. Coat the substrate evenly using a roller or a brush.

Allow for the primer to dry for at least three hours and continue with the plaster application.

CONSUMPTION

1lt/8-10m²/coat, depending on the absorbency of the substrate.



