

6.3 Primers for plaster & concrete

DUROSTICK No40 PVA PRIMER Interior use primer

PROPERTIES

Vinyl based, water soluble, flexible primer for interior use.

It stabilizes porous surfaces to be painted. It prepares and increases the adhesion between the substrate with the emulsion and acrylic paints. By reducing the absorption of plaster and drywall, less amount of paint is needed to complete the project. It is odorless and it is recommended for use, even in areas that are not adequately ventilated. Friendly to human and the environment.

APPLICATIONS

PVA PRIMER is applied on indoor building surfaces coated with plaster/render, on skim coated surfaces as well as surfaces lined with chipboard and drywall. Alternatively, AQUAFIX and SOLVENT BASED PRIMER of

DUROSTICK is also recommended for drywall surfaces.

USE

1. Surface preparation

Surfaces to be primed have to be clean, dry, free from dust and loose materials.

2. Application

Mix well before use. Apply it with a brush or a roller, at ambient temperatures, from 5°C to 35°C. Dilute with clean, cool water at a ratio of 1 part PVA PRIMER to two parts water. Paint over it after 8 hours, depending on the ambient conditions (temperature - humidity).

CLEANING

Clean all tools with water and detergent solution immediately after use.



pic. 1



pic. 2

TECHNICAL SPECIFICATIONS

Form - Color	Concentrated emulsion- White, becomes transparent when dry
Density	1.00±0.05 kg/lt
Application temperature	From +5°C to +35°C
Drying time	3 hours at 20°C

Odorless, friendly to human and the environment

V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/h: 'Binding primers' Type WB): 30 gr/lt (2010). Ready to use product contains maximum 29 gr/lt V.O.C.

CONSUMPTION

1lt/12-15m², on properly prepared surfaces, depending on the absorbency of the surface.

STORAGE

Store in places protected from frost for at least 18 months from production date.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

Carton box with 12 pcs of 750ml each one
3lt, 25lt containers