



DECLARATION OF PERFORMANCE

DoP [EN] No. 007 DURO-CPR-7-2013

- Unique identification code of product-type:
PLUS reinforced tile adhesive.
- Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
The coding shown on the packaging is the production date of the product.
- Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
Enhanced adhesive with reduced slip and extended open time. Deformable. C2TE/S1.
- Name, registered name or registered trade mark and contact address for the manufacturer as required to Article 11(5):
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE
- Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:
Not applicable.
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3.
- In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 12004: 2007+ A1: 2012
The notified control laboratory MIRTEC with number NB 0437 has carried out initial tests to determine the product type under system 3 and issued a test report with number 3354.
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable.
- Declared performance:

Essential characteristics	Declared performance	Harmonised standard Appropriate /Technical Documentation	
Reaction to fire:	Euroclass (A1/A1_{fl})		
Bond Strength as:	> 1N/mm²	EN 1348 8.2	EN 12004:2007+A1:2012
• Tensile adhesion strength			
Durability as:			
Tensile adhesion strength after:			
• heat ageing	> 1N/mm²	EN 1348 8.4	
• water immersion:	> 1N/mm²	EN 1348 8.3	
• freeze-thaw cycles:	> 1N/mm²	EN 1348 8.5	
Dangerous substances	See MSDS		

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Evdoxia Kafritsa

Aspropyrgos 12/12/2016

R&D Manager, QC mortars lab



DUROSTICK S.A

ASPROPYRGOS ATHENS PC: 19300

GREECE

07

EN 12004:2007+ A1:2012

PLUS

DoP No.: 007

C2TE/S1

Enhanced adhesive with reduced slip and extended open time

Deformable

Interior –exterior use

- Reaction to fire: Euroclass A₁
- Release of dangerous substances: see MSDS

Bond Strength as:

- Tensile adhesion strength : $\geq 1.00 \text{ N/mm}^2$

Durability for:

- Tensile adhesion strength
after heat ageing: $\geq 1.00 \text{ N/mm}^2$
- Tensile adhesion strength
after water immersion: $\geq 1.00 \text{ N/mm}^2$
- Tensile adhesion strength
after freeze-thaw cycles: $\geq 1.00 \text{ N/mm}^2$