

PVC PRIMER



Primer for PVC pipes



PROPERTIES

Cleaner of PVC plastic pipes.

Removes oils, grease, grease, slightly corroding the gloss of the pipes. In this way the PVC glue adheres more strongly during the application process, offering even stronger bonding. The container cap has a built-in round brush for easy applications.

APPLICATIONS

The need for a clean welding surface of plastic pipes in networks under pressure, but also in general applications, ensures careful work, without problems.

If PVC adhesives have begun to lose their workability due to evaporation, their fluidity is restored by mixing the required amount of PVC PRIMER and vigorously shaking the adhesive package.

USE

1. Surface preparation

Using a dry cloth, remove any filth, soil or mud, if any, from the surfaces to be welded.

2. Application

With the help of the special brush we apply the PVC PRIMER around the perimeter, both inside and outside, where the glue will be applied. As soon as the PVC PRIMER is dry the surfaces are ready to be welded.

CONSUMPTION

Depending on the diameter of the pipe and the necessity for cleaning it.

STORAGE

Store in tightly closed container, in shaded places, away from any heat source, for at least 24 months from production date.

SAFETY DIRECTIONS

The product is classified as highly flammable and harmful. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

PACKAGING

Carton box with 12 pcs of 236ml each one

PVC PRIMER



Primer for PVC pipes

TECHNICAL SPECIFICATIONS

Form	Liquid
Color	Transparent
Density	0.85±0.05 kg/lit
Cleaning and thinning ability	Only for PVC pipes, fittings and PVC GLUE
Application temperature	From +4°C to +35°C

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211
60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30
210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310
797 365, Fax: +30 2310 797 367
Email: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.