

DUROSTICK RELIEF



Texture coating



PROPERTIES

Highly durable, protective and decorative textured coating and white finish. Its composition contains special purpose acrylic resins that impart strong adhesion, excellent resistance to atmospheric pollutants and adverse weather conditions. It applies easily without any paint lapping.

APPLICATIONS

DUROSTICK RELIEF is suitable for any new and existing surface made of plaster and concrete, wood, chipboard, as well as any other surface, after proper preparation.

Exceptional for coastal structures due to its waterproofing properties. Ideal for the easy creation of a variety of decorative patterns, simply by using styling foam and/or rubber rollers on the coated surfaces. This styling option will cover construction and finishing defects, on interior and exterior surfaces.

USE

1. Substrate preparation

Concrete and marble surfaces must be dry, free of loose materials, oils, dust, and at least 30 days from their construction.

Coated surfaces with RELIEF that are sound, two coats with DUROSTICK acrylic paints (MINERAL SURFACE PAINT, 100% acrylic paint that is mold resistant, or 10 YEARS WARRANTY paint) are enough to maintain the texture and finish.

For peeling surfaces, remove all loose materials and prime using 100% ACRYLIC PRIMER, or micromolar stabilizer AQUAFIX of DUROSTICK.

For spackling, apply DUROSTICK GRANULAR to cover all defects ranging from 1mm and up to 20mm thick. Continue by priming the surfaces.

Surfaces with detached RELIEF sections, remove any loose sections with a putty knife and prime them.

DUROSTICK RELIEF



Texture coating

2. Application

Mix very well before use. Apply DUROSTICK RELIEF with an ordinary painting roller. Before the decorative coating dries, use a texture paint foam roller to create the desired texture and style. Recoat using the acrylic paint 10 YEARS WARRANTY or MINERAL SURFACE PAINT OF DUROSTICK..

CLEANING

Clean all tools with water and detergent solution, immediately after use.

PERFORMANCE

Approximately 1-1.5m²/lt per coat, depending on the texture, the absorbency of the surface and the application method.

STORAGE

Store in places protected from sunlight and frost, for at least 18 months from production date.

NOTE

If needed, it is recommended to clean the freshly painted surface that DUROSTICK RELIEF was used, with a soft sponge and mild detergent, 15 days after its application.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

LIMITATION OF USE

Do not apply if there is a chance of rain or frost within the next 18 hours.

PACKAGING

5kg & 15kg containers

TECHNICAL SPECIFICATIONS	
Colors	White that does not yellow over time
Shades	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors.
Washability	> 15,000 cycles (per DIN 53778)
Gloss	Matte
Drying time	1 hour (touch dry), depending on the ambient conditions
Recoating time	4-5 hours depending on the ambient conditions
Application temperature	From +8°C to +35°C
Flammable	No
V.O.C. (Volatile Organic Compounds): <i>Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/c: 'Coatings for exterior walls of mineral substrate' Type WB): 40gr/lt (2010). The ready to use product contains maximum 34gr/lt V.O.C.</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612
 THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367
 E-mail: info@durostick.com