

ROMIX 100% ACRYLIC



For plaster & concrete surfaces



PROPERTIES

Acrylic paint with high coverage, performance and whiteness, with strong adhesion. Recommended for interior and exterior use, in places requiring frequent repainting. Easy to work with, dries quickly and is resistant to air pollutants. It 'allows' the breathability of surfaces where it is applied, allowing water vapour permeable. It is a reliable and economical solution for professionals who undertake spaces that need frequent maintenance.

APPLICATIONS

ROMIX 100% ACRYLIC is suitable for new or existing surfaces of plaster, concrete and asbestos-cement bricks or for first coatings when a change of shade is desired. It is also ideal for sprucing up places that require frequent maintenance painting, such as schools, public buildings, hotels but also large public and small private projects. Ideal solution for areas exposed to graffiti, etc.

USE

1. Substrate preparation

Concrete and marble based plaster must be dry and free from loose materials and oils. At least 30 days must have passed from their construction completion

2. Application

Dilute ROMIX 100% ACRYLIC with water at a ratio of up to 5%, depending on the substrate, and stir well. Apply with brush, roller or airless spray gun in 2-3 coats. Apply each additional coat, after the previous one is completely dry.

CLEANING

Clean all tools with water and detergent solution, immediately after use.

PERFORMANCE

Approximately 9-12m²/lt per coat, depending on the texture, the absorbency of the surface and the application method.

ROMIX 100% ACRYLIC



For plaster & concrete surfaces

STORAGE

Store in places protected from sunlight and frost, for at least 18 months from production date.

NOTE

If needed, it is recommended to clean the freshly painted surface that ROMIX 100% ACRYLIC was used with a soft sponge and mild detergent, 20 days after its application.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

LIMITATION OF USE

Do not apply with temperatures below +8°C or if there is a chance of rain or frost within the next 12 hours.

PACKAGING

Carton box with 12 pcs of 750ml each one
3lt container (on a 100 pcs pallet)
9lt container (on a 48 pcs pallet)

TECHNICAL SPECIFICATIONS

Color	White, that does not yellow over time
Shades	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors. The Pal and Dark bases are colored via the COLOR COLLECTION System in any desired color
Washability	> 10,000 cycles (per DIN 53778)
Gloss	Matte
Drying time	1 hour (touch dry), depending on the ambient conditions
Recoating time	4-5 hours, depending on the ambient conditions
Application temperature	From +8°C to +35°C
Flammable	No
V.O.C. (Volatile Organic Compounds): <i>Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/c: 'Coatings for exterior walls of mineral substrate' Type WB): 40gr/lit (2010). The ready to use product contains maximum 39gr/lit V.O.C.</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:
+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55
98 350, Fax: +30 210 55 99 612
THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30
2310 797 365, Fax: +30 2310 797 367
E-mail: info@durostick.com