

DUROSTICK RUST FREE



Anticorrosive and lubricant spray



PROPERTIES

Refined lubricating spray that is long lasting. It presents exceptional penetrating action and dehumidification ability. It quickly dissolves rust and lubricates at the same time. It restores full and easy operation on tools and mechanisms. It creates an invisible film that ensures protection from future corrosion. It works preventively against rust ensuring the fluid movement of mechanical parts, while repelling moisture at the same time.

APPLICATIONS

RUST FREE lubricating spray of DUROSTICK is suitable for instant removal of stuck parts due to corrosion and rust, restoring operation to screws with nuts, bolts, pipe thread connections, on any type of metal mechanisms and tools. It assists the easy disassemble of all rusted elements, as it penetrates into the connections and loosens the accessories. It helps remove moisture and water from the electrical parts of various equip-

ment. Ideal for many uses in workshops and industry plants. Necessary for any houses, gardens, automobiles, engines bikes and boats.

USE

Shake the can very well, and spray by squeezing the trigger lightly. To get easier access to hard to reach areas, please use the thin straw attachment.

STORAGE

Store in dry and shaded places, for at least 24 months from production date.

SAFETY DIRECTIONS

The product is classified as extremely flammable. It is recommended to keep away from the reach of children. Before use, refer to the cautions on the product label or the Material Safety Data Sheet.

DUROSTICK RUST FREE



Anticorrosive and lubricant spray

PACKAGING

Carton box with 12 pcs of 200ml each one

Carton box with 12 pcs of 400ml each one

TECHNICAL SPECIFICATIONS	
Form - Color	Low viscosity lubricant - Transparent
Density	0.83±0.04kg/lit
Does not harm the ozone layer	
Does not contain CFC (chlorofluorocarbons)	
Flammable	Yes

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:

+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55

98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30

2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.