

DUROSTICK RUST REMOVER



Powerful rust remover that works on any metal surface



PROPERTIES

Very powerful rust remover from any kind of metal surface, easily and quickly, avoiding scrubbing with a wire brush or other mechanical means. Dissolves any surface rust created over time, but also created from rain, moisture, and salt air, leaving surfaces ready to be primed and painted.

APPLICATIONS

DUROSTICK RUST REMOVER removes rust from metal doors, railings, car and boat sheet metal, flatbeds of trucks and of agricultural vehicles. Effectively cleans industrial and agricultural tools, chains and padlocks, pliers, cutters, scissors, screws, nuts, and other tools that have been affected by rust. Quickly cleans rust stains from tiles, natural stones, and exposed concrete rebars (steel reinforcement)

USE

1. Surface preparation

Remove from the surface all loose rust flakes (if any).

2. Application

- During use and while rinsing, it is highly recommended to use protective goggles and plastic gloves.
- Shake well before use.
- Apply the material as is, in a thick coat using a brush or use it as dip and allow for it to act for about 10 minutes.
- Rinse thoroughly with plenty of water.
- On heavily rusted surfaces, it may be necessary to repeat the process.
- Once all the rust is removed, the surface or item is cleaned and after drying, apply a coat of NATURAL RED LEAD of DUROSTICK for proper anti-corrosion protection, a coat of METAL PRIMER of DUROSTICK and one to two coats of DUROLUX or DUROLUX AQUA of DUROSTICK.

DUROSTICK RUST REMOVER



Powerful rust remover that works on any metal surface

NOTES

- Make sure that product residues do not accumulate near plants because there is a risk of their destruction.
- Before applying on polished marbles and mosaic, dilute with 50% clean water and test it. Apply it on a hidden-from-view area (preventively), to make sure the application does not dull or corrode the surface.

CONSUMPTION

Depending on the application.

STORAGE

Store in shaded places, protected from sunlight and frost, for at least 18 months from production date.

SAFETY DIRECTIONS

The product is classified as corrosive. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

PACKAGING

Carton box with 12pcs of 500ml each one
Carton box with 12pcs of 1lt each one
5lt container

TECHNICAL SPECIFICATIONS

Form - Color	Liquid - Blue
Density	1.30±0.05kg/lt
pH	0-1

Contains: More than 10% phosphoric acid, less than 5% non-ionic surfactants & less than 5% anionic surfactants, among others.

*Permit No. by General Chemical State Laboratory
ELEFSIS 3093/2008*

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:
+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55
98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30
2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com