

SEALANT



For foam insulation products



PROPERTIES

White acrylic elastomeric sealant, suitable for protecting foam insulation pipes. Use it to maintain the flexibility of the foam insulating pieces by preventing the sun from damaging them (drying out), leading to their gradual destruction. It contains powerful UV filters that prevent the bursting or peeling of the sealant.

APPLICATIONS

DUROSTICK SEALANT and paint for foam insulation, ensures the protection of all types of foam insulation after their installation over exterior and interior copper, iron, PVC or polypropylene piping.

Ideal for the protection of foam insulation in solar water heaters and other plumbing installations. It is necessary to protect the new foam insulation to avoid disintegration (a common occurrence). The same protection is needed for previously installed, but in good condition, foam insulation pieces. Use it also to seal the holes created from any type of bracket support, on the roof surface, or the walls. The product is white that can be colored using the Measuring System for Shade

Rendering, DUROCOLOR of DUROSTICK (syringe packaging of 20ml each one), capable of creating 120 permanent colors

USE

1. Surface preparation

All surfaces must be clean, dry and free from dust and loose materials.

2. Application

Stir the product and apply one to two coats, with a difference of 3-4 hours between coats.

NOTES

- It prevents damage by the pecking of birds to the foam insulation. Its excellent adhesion to foam insulation makes it a more secure 'system', even from the coated foam insulation.
- After drying, the product is harmless to health.

LIMITATION OF USE

Do not apply if there is a chance of rain for the next 12 hours.

SEALANT



For foam insulation products

CONSUMPTION

1.0-1.5kg/m² per coat

STORAGE

Store in places protected from frost for at least 24 months from production date.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and national legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek medical advice and show the container or label.

PACKAGING

Carton box with 12 pcs. of 1kg each one

TECHNICAL SPECIFICATIONS	
Form - Color	Viscous liquid - White
Density	1.50±0.05kg/lt
Deformability (Per ASTM D412)	After curing for 8 days and to a membrane of 1mm thick, the elongation at break was found at 300%
Application temperature	From +8°C to +40°C
Temperature resistance	From -20°C to +80°C
Water tightness	7atm per DIN 1048

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367

Email: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.