



## DECLARATION OF PERFORMANCE

DoP [EN] No. 097 DURO-CPR-9-2014

- Unique identification code of product-type:  
**D U R O S T I C K S I L I C O N E**
- Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):  
**The six-digit number printed on the package corresponds to the Batch Production Number of product.**
- Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:  
**Silicone sealant.**
- Name, register name or register trade mark and contact address for the manufacturer as required to Article 11 (5):  
**DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE.**
- Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2):  
**Not applicable**
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 3**
- In case of the declaration of performance concerning a construction product covered by a harmonized standard :  
**EN 15651 - 1, EN 15651 - 2, EN 15651 - 3**  
The notified testing laboratory Tecnia Research Innovation with No. 1292 conducted tests to determine the type of product under system 3 and issued a test report No. 14\_06000-a.
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
**Not applicable**
- Declared performance:

### PROCEDURE (IN ACCORDANCE WITH ISO 8340)

Essential Characteristics	Declared performance	Harmonized standard
Reaction to fire	Class E	
Release of Chemicals	None	See product safety data sheet
Water Tightness & Air Tightness as determined by :		
Resistance to flow	≤3mm	EN15651-1
Loss of volume	≤40%	EN15651-1
Adhesion/Cohesion at maintained extension after immersion in water	No Failure	EN15651-1
Adhesion/Cohesion at maintained extension for non-	No Failure	EN15651-1

structural sealants used in joints in cold climate areas (-30°C)		
Adhesion/Cohesion properties after exposure to heat water and artificial light	Pass Glass	EN15651-1
Elastick recovery	≥60%	EN15651-2
Microbiological growth	1	EN15651-3
Durability	Pass	EN15651-1.2.3

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Dr. Aristides Koutsibelis

Aspropyrgos 22/09/2014

R&D Manager, QA fluids lab

# CE

**DUROSTICK S.A**  
**ASPROPYRGOS ATHENS PC: 19300**  
**GREECE**  
**14**

**EN 15651-1.2.3**

**SILICONE**  
**DoP No. : 097**

<b>Reaction to fire:</b>	<b>Class E</b>
<b>Release of Chemicals:</b>	<b>None</b>
<b>Resistance to flow:</b>	<b><math>\leq 3\text{mm}</math></b>
<b>Loss of volume:</b>	<b><math>\leq 45\%</math></b>
<b>Determination of tensile properties after immersion in water (23°C):</b>	<b><math>\geq 25\%</math></b>
<b>Durability:</b>	<b>Pass</b>