

# SOLDERING PASTE



Flux for cleaning copper pipes & fittings



## PROPERTIES

Viscous soldering paste for cleaning copper pipes and fittings. It cleans copper without scratching it and protects it from tarnish, ensuring strong and watertight seals. It facilitates the solder absorption into the pipe and fitting joints.

## APPLICATIONS

It works best with copper, brass, zinc, tin metals and alloys. Suitable for all soft solders, used for copper piping systems as well as heating and cooling piping systems.

## USE

The container cap has a built-in round brush for quick and easy applications of the product, without dripping. Apply a thin layer of the paste to all the parts that will be welded, at their contact sections. Make sure that all the welding parts have a tight fit. Heat the adjacent surfaces with a torch to the boiling point of the paste and push the solder into the joint. As the welded joint begins to cool, carefully clean it using a damp cloth.

## CONSUMPTION

Depending on the application

## STORAGE

Store in shaded places for at least 36 months from the production date.

## SAFETY DIRECTIONS

The product is corrosive and must be kept locked, away from the reach of children. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

## PACKAGING

Carton box with 24pcs of 125gr each one

## TECHNICAL SPECIFICATIONS

Form - Color                      Thick paste - Yellow

Flammable                        No

Does not contain lead

**DUROSTICK S.A.**, MANUFACTURING OF ADHESIVES, PAINTS & MORTARS  
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612, THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367, Email: info@durostick.com